

DUPLICATE

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF
THE SIXTH STANDARD PARALLEL NORTH, THROUGH RANGE 8 EAST,
THE WEST AND NORTH BOUNDARIES, THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF CERTAIN SECTIONS,
AND THE SURVEY OF THE SUBDIVISION OF CERTAIN SECTIONS,
TOWNSHIP 25 NORTH, RANGE 8 EAST,
OF THE SIXTH PRINCIPAL MERIDIAN
IN THE STATE OF NEBRASKA.

EXECUTED BY

RYAN R. LORENZEN

CADASTRAL SURVEYOR

Under Special Instructions dated MAY 11, 2011, approved MAY 11, 2011, which provided for the surveys included under Group Number 175, Nebraska, and assignment instructions dated MAY 11, 2011.

Survey commenced MAY 11, 2011

Survey completed May 3, 2012

INDEX DIAGRAM

Township 25 North, Range 8 East

10						
8 5	49 4	43 3	38 2	28 1 25	EAST	
8	9	10	11 37	23 12 21		MERIDIAN
17	16 48	15 42	14 36 34	17 13		
20	21	40 22	23	24		GUIDE
29	28 46	27	26 33 31	25 15		FIRST
32	44 33	34	29 35	12 36		
6 5 2						

SIXTH STANDARD PARALLEL NORTH

INDEX DIAGRAM

Township 25 North, Range 8 East

Dependent Resurvey, Subdivision of Section 1	Page 50
Subdivision of Section 1	Page 53
Dependent Resurvey, Subdivision of Section 3	Page 55
Subdivision of Section 3	Page 57
Dependent Resurvey, Subdivision of Section 4	Page 58
Subdivision of Section 4	Page 60
Dependent Resurvey, Subdivision of Section 5	Page 62
Subdivision of Section 5	Page 64
Dependent Resurvey, Subdivision of Section 12	Page 65
Subdivision of Section 12	Page 67
Dependent Resurvey, Subdivision of Section 13	Page 70
Subdivision of Section 13	Page 73
Dependent Resurvey, Subdivision of Section 14	Page 74
Subdivision of Section 14	Page 76
Dependent Resurvey, Subdivision of Section 15	Page 79
Subdivision of Section 15	Page 80
Dependent Resurvey, Subdivision of Section 21	Page 81
Subdivision of Section 21	Page 82
Dependent Resurvey, Subdivision of Section 26	Page 82
Subdivision of Section 26	Page 86
Dependent Resurvey, Subdivision of Section 33	Page 87
Subdivision of Section 33	Page 90
Dependent Resurvey, Subdivision of Section 34	Page 90
Subdivision of Section 34	Page 94
Dependent Resurvey, Subdivision of Section 36	Page 95
Subdivision of Section 36	Page 97

T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>The following field notes are those of the dependent resurvey of portions of the Sixth Standard Parallel North, through Range 8 East, the west and north boundaries, the subdivisional lines, and the subdivision of certain sections; and the survey of the subdivision of certain sections, of Township 25 North, Range 8 East, of the Sixth Principal Meridian, Nebraska.</p> <p>Charles A. Manners surveyed the First Guide Meridian East (east boundary) and the Sixth Standard Parallel North, through Range 8 East, (south boundary) in 1855. Theodore H. Barrett resurveyed the east and south boundaries, setting 1/16 section corners, in 1866, and surveyed the remaining exterior boundaries, the subdivisional lines, and subdivided the sections in 1867. Richard A. Kohler dependently resurveyed portions of the east and north boundaries, the subdivisional lines, the subdivision of certain sections, and surveyed the subdivision of certain sections, in 1993. Ryan R. Lorenzen dependently resurveyed the east boundary during the dependent resurvey of T. 25 N., R. 9 E., in 2001-03. Ryan R. Lorenzen dependently resurveyed portions of the north boundary during the dependent resurvey of T. 26 N., R. 8 E., in 2002-03. Ryan R. Lorenzen dependently resurveyed portions of the west boundary, the subdivisional lines, the subdivision of certain sections, and surveyed the subdivision of certain sections, in 2008.</p> <p>Birney C. Wolley, Civil Engineer, was hired by Thurston County Commissioners to remonument corners with vitrified clay tile in 1910, according to courthouse records filed by Wilbur A. Racely, Thurston County Surveyor, in 1948. Partial field note records of these surveyors are maintained at MLS and Associates, P.L.C. (formally Schieuer Surveying, P.C.), in Sioux City, Iowa. Later surveyors at times also adopted this type of monumentation and the lack of individual markings makes positive identification uncertain. Numerous state, county and private surveys have been executed throughout the township as recorded with the Nebraska State Surveyor's Office, the Nebraska State Department of Roads and the Thurston County Courthouse. When appropriate, specific references are made to these surveys herein. In some situations, exact reference to a particular surveyor or survey date is not possible due to courthouse recording methods used. In analyzing such items as time line, hand writing, nearby identifiable surveys, etc., an attempt has been made to attribute these surveys in question to a particular surveyor and/or date, and where applicable such attributed reference is made herein.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 2009, and the Special Instructions for Group Number 175, Nebraska, dated May 11, 2011.</p>
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains

Preliminary to the resurvey, the lines of the previous surveys were retraced and diligent search was made for all corners and other calls of the field note record. Identified corners were remonumented in their original positions; lost corners were reestablished and monumented at proportionate positions based on the latest official record, but only after exhausting every possibility of finding direct evidence of such corners. The retracement data were thoroughly verified and only true line field notes are given herein, which refer to the completed survey.

The survey was executed with TRIMBLE Models 5700 and 5800 Global Positioning System (GPS) receivers, a TRIMBLE Model TSC2 data controller, a WILD Model T1000 electronic theodolite, a WILD Model DI1600 electronic distance meter, and by chaining methods. The GPS procedures used were in accordance with IM No. 2010-094, "Incorporating Standards for the Positional Accuracy of Cadastral Surveys When Using Global Navigation Satellite Systems," dated April 1, 2010. The instruments were maintained in proper adjustment at all times. The directions of all lines refer to the true meridian as determined by GPS observations. GPS control network and supporting data are contained in the official group file.

The geographic position of the southeast corner of the township, based on NAD 83 (CORS 96) and determined by GPS methods, is:

Latitude 42° 05' 23.290" N., Longitude 96° 27' 46.380" W.

The mean magnetic declination is 3½° E.

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

(Restoring the resurvey executed by
Theodore H. Barrett in 1866)

Beginning at the cor. of Tps. 24 and 25 N., Rs. 8 and 9 E., monumented with a steel nail marker, 3/8 in. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.

N. 89° 48' W., on the S. bdy. of sec. 36.

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

Chains	<p>Over rolling terrain, along gravel surfaced road.</p>
19.965	<p>Point for the standard E. 1/16 sec. cor. of sec. 36, identical with the E. 1/16 sec. cor. of sec. 1 only, T. 24 N., R. 8 E., at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.</p>
39.93	<p>The standard 1/4 sec. cor. of sec. 36, identical with the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 8 E., monumented by person(s) unknown with an angle iron, 18 ins. long, 1¼ ins. wide, firmly set 18 ins. below gravel surfaced road extending E. and W., in projection of abandoned fences from the N. and S. This position is in harmony with a position recorded in Surveyor's Record Book No. 1, p. 201, in the Thurston County Courthouse, and accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p> <div style="text-align: center;"> <p>SC T25N R8E 1/4 S 36</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 1 T24N 2011</p> </div> <p>Deposit the angle iron inside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 3¾° E., 43.5 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S36 28.7 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 53° E., 78.0 lks. dist., with brass cap mkd. RM T24N R8E 1/4 S1 51.5 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

Chains	<p>N. 89° 50' W., beginning new measurement.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>19.73 Point for the standard W. 1/16 sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.</p> <p>39.46 The standard cor. of secs. 35 and 36, monumented by person(s) unknown with a solid iron axle, 30 ins. long, 1 in. diam., with 3½ in. diam. worm gear on top, firmly set 14 ins. below intersection of gravel surfaced road extending E. and W., with E. side of dirt surfaced roads extending N. and S., with decayed wood fragments alongside. This position is recorded in Official Record of Surveys Book No. 3, p. 11, and Surveyor's Record Book No. 1, p. 255, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop the inverted iron axle, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> SC T25N R8E <u>S 35 S 36</u> </div> <p style="text-align: center;">2011</p> <p>Bury the wood fragments in a plastic bag alongside the iron post.</p> <p>from which</p> <p style="margin-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 33¼° E., 54.9 lks. dist., with brass cap mkd. RM T25N R8E S36 36.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="margin-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 52° W., 115.7 lks. dist., with brass cap mkd. RM T25N R8E S35 76.4 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr style="width: 60%; margin-left: auto; margin-right: auto;"/>
---------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>From the standard W. 1/16 sec. cor. of sec. 35, monumented by person(s) unknown with an iron pipe, 32 ins. long, 1¼ ins. diam., firmly set 28 ins. below gravel surfaced road extending E. and W., in projection of divide between cultivated fields from the N. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R8E W 1/16 S 35 ----- 2011</p> <p>Deposit the iron pipe inside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 0¾° E., 54.8 lks. dist., with brass cap mkd. RM T24N R8E SC W1/16 S2 36.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 0¾° W., 58.0 lks. dist., with brass cap mkd. RM T25N R8E SC W1/16 S35 38.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>N. 89° 51' W., on the S. bdy. of sec. 35.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>19.15 Creek, drains NNW.</p> <p>19.995 Point for the standard cor. of secs. 34 and 35, at proportionate distance, falls in gravel surfaced road extending E. and W.; there is no remaining evidence of the original cor. or the monument recorded in the Thurston County Courthouse.</p>
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

Chains	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R8E <u>S 34 S 35</u></p> <p style="text-align: center;">2011</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 0¼° W., 50.0 lks. dist., with brass cap mkd. RM T24N R8E SC S2 33.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 1¼° W., 50.1 lks. dist., with brass cap mkd. RM T25N R8E SC S34 33.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located 32 lks. W. of W. edge of planking on road bridge.</p> <hr style="width: 60%; margin-left: 0;"/> <p>N. 89° 51' W., on the S. bdy. of sec. 34.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>1.00 Intersection of gravel surfaced roads, bears NNE., E., SSW. and W.</p> <p>9.88 Center of railroad track, bears NNE. and SSW.</p> <p>19.995 The standard E. 1/16 sec. cor. of sec. 34, monumented by person(s) unknown with an iron pipe, 20 ins. long, 1¾ ins. diam., firmly set 32 ins. below N. lane of gravel surfaced road extending E. and W., with glass fragments around base. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>
---------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

Chains	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p> <p style="text-align: center;">SC T25N R8E E 1/16 S 34 ----- 2011</p> <p>Deposit the iron pipe inside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 0¼° E., 51.9 lks. dist., with brass cap mkd. RM T24N R8E SC E1/16 S3 34.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 0¼° W., 29.7 lks. dist., with brass cap mkd. RM T25N R8E SC E1/16 S34 19.6 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 89° 52' W., beginning new measurement.</p> <p>Over rolling terrain, along gravel surface road.</p> <p>19.98 The standard 1/4 sec. cor. of sec. 34, monumented by person(s) unknown with an iron pipe, 45 ins. long, 1¼ ins. square, firmly set 18 ins. below gravel surfaced road extending E. and W., with glass, crockery and wood fragments around base, with an iron pipe, 20 ins. long, 1½ ins. diam., set alongside, in projection of fences from the N. and S., as recorded in Surveyor's Record Book No. 1, p. 203, in the Thurston County Courthouse. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop the reset square iron pipe, with brass cap mkd.</p>
---------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the
Sixth Standard Parallel North, through Range 8 East,
Sixth Principal Meridian, Nebraska

Chains	<div style="text-align: center;"> SC T25N R8E 1/4 S 34 <hr style="width: 10%; margin: 0 auto;"/> 2011 </div> <p>Bury the glass, crockery and wood fragments in a plastic bag alongside the iron post. Remove the 1½ ins. diam. iron pipe from the vicinity.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 0½° E., 52.1 lks. dist., with brass cap mkd. RM T25N R8E SC 1/4 S34 34.4 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 0¾° W., 50.0 lks. dist., with brass cap mkd. RM T24N R8E SC 1/4 S3 33.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Note: The records in the Thurston County Courthouse appear to depict that the recovered monumentation was inappropriately utilized for both the standard 1/4 sec. cor. of sec. 34, and the 1/4 sec. cor. of sec. 3 only, even though the official record shows a closing distance of 47 lks. between the two. After tying to surrounding evidence, it was concluded that the monument recovered in fact represented the standard cor. position.</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey, Portion of the West Boundary, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the cor. of secs. 1, 5, 8 and 12, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 2008 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <p>N. 0° 03' W., bet. secs. 1 and 5.</p>
---------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the West Boundary,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	Over rolling terrain, across cultivated field.
20.005	<p>Point for the S. 1/16 sec. cor. of secs. 1 and 5, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R7E R8E S 1/16 S 1 S 5 2011</p>
40.01	<p>The 1/4 sec. cor. of secs. 1 and 5, monumented in 1988 by Wayne W. Wheeler, Nebraska Registered Land Surveyor No. 211, with a steel reinforcement rod, 30 ins. long, 5/8 in. diam., firmly set 6 ins. below the surface of cultivated field, with aluminum cap mkd. GOVERNMENT CORNER TWP 25 R7 R8 1 5 LS211 and a cross. This position is recorded in Plat Book No. 5, p. 45, in the Thurston County Courthouse, and is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R7E R8E 1/4 S 1 S 5 2011</p> <p>Deposit the steel reinforcement rod inside the iron post.</p> <p>Cor. is located in projection of fence from the E.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 0° 03' W., beginning new measurement.</p> <p>Over rolling terrain, across cultivated field.</p>
20.00	Point for the N. 1/16 sec. cor. of secs. 1 and 5, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.

Dependent Resurvey, Portion of the West Boundary,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
40.00	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R7E R8E N 1/16 S 1 S 5 2011</p> <p>The cor. of Tps. 25 and 26 N., Rs. 7 and 8 E., monumented with an aluminum rod, 5/8 in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 26 N., R. 8 E.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the North Boundary, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by Richard A. Kohler in 1993)</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an aluminum rod, 5/8 in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <p>N. 89° 51' W., bet. secs. 4 and 33.</p> <p>Over rolling terrain, along gravel surfaced road.</p>
20.055	<p>Point for the E. 1/16 sec. cor. of secs. 4 and 33, at proportionate distance, falls in gravel surfaced road extending E. and W.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T26N R8E S 33 E 1/16—— S 4 T25N 2011</p>

Dependent Resurvey, Portion of the North Boundary,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 5¼° E., 71.0 lks. dist., with brass cap mkd. RM T26N R8E E1/16 S33 46.9 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 1¾° E., 49.1 lks. dist., with brass cap mkd. RM T25N R8E E1/16 S4 32.4 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located in projection of fence from the S.</p>
40.11	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an aluminum rod, 5/8 in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <hr/> <p>N. 89° 50' W., beginning new measurement.</p>
20.065	<p>Over rolling terrain, along gravel surfaced road.</p> <p>Point for the W. 1/16 sec. cor. of secs. 4 and 33, at proportionate distance, falls in gravel surfaced road extending E. and W.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T26N R8E S 33 W 1/16—— S 4 T25N 2011</p>

Dependent Resurvey, Portion of the North Boundary,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 75¼° E., 134.7 lks. dist., with brass cap mkd. RM T26N R8E W1/16 S33 88.9 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 0½° E., 56.5 lks. dist., with brass cap mkd. RM T25N R8E W1/16 S4 37.3 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>
40.13	<p>The cor. of secs. 4, 5, 32 and 33, monumented with an aluminum rod, ⅝ in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 26 N., R. 8 E.</p>
	<hr/> <p style="text-align: center;">Dependent Resurvey, Portion of the Subdivisional Lines, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/>
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 18' E., bet. secs. 35 and 36.</p> <p>Over rolling terrain, along dirt surfaced road.</p>
20.05	<p>Point for the S. 1/16 sec. cor. of secs. 35 and 36, at proportionate distance, falls in dirt surfaced road extending N. and S., falls in projection of fence from the E.; there is no remaining evidence of the original cor. Point not monumented.</p>
40.10	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance, falls in dirt surfaced road extending N. and S.; there is no remaining evidence of the original cor. or the cor. recorded in the Thurston County Courthouse.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 35 S 36 2011</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 87¼° E., 53.0 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S36 35.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 88° W., 39.6 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S35 26.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Road surface gradually becomes graveled from this point.</p> <p>60.15 Point for the N. 1/16 sec. cor. of secs. 35 and 36, at proportionate distance, falls on W. edge of gravel surfaced road extending N. and S.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E N 1/16 S 35 S 36 2011</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 89¾° E., 74.2 lks. dist., with brass cap mkd. RM T25N R8E N1/16 S36 49.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p> <p>80.20</p>	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 88½° W., 31.9 lks. dist., with brass cap mkd. RM T25N R8E N1/16 S35 21.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located 19 lks. S. of projection of fence from the E., and 1.75 chs. S. of projection of second fence from the E.; fences surround grove of trees.</p> <p>The cor. of secs. 25, 26, 35 and 36, monumented by person(s) unknown with an iron pipe, 36 ins. long, 1 in. diam., firmly set 24 ins. below intersection of gravel surfaced roads extending N., E., S. and W., with an iron rod, ½ in. diam., driven in the center, with vitrified clay tile and glass fragments and bottom 6 in. section of wood stake buried alongside. This position is recorded in Official Record of Surveys Book No. 3, p. 11, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the roads, atop the inverted iron pipe with iron rod, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T25N R8E</td> </tr> <tr> <td style="text-align: center;">S 26</td> <td style="text-align: center;">S 25</td> </tr> <tr> <td style="text-align: center;">S 35</td> <td style="text-align: center;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center;">2011</td> </tr> </table> <p>Bury the tile, glass and wood fragments in a plastic bag alongside the iron post.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 47¼° W., 60.0 lks. dist., with brass cap mkd. RM T25N R8E S35 39.6 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>	T25N R8E		S 26	S 25	S 35	S 36	2011	
T25N R8E									
S 26	S 25								
S 35	S 36								
2011									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 37¾° W., 74.5 lks. dist., with brass cap mkd. RM T25N R8E S26 49.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of Tp., monumented with a steel nail marker, ⅜ in. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>From this point, GPS Control Point No. 2 (CP02), T. 25 N., R. 9 E., utilized during the course of this survey, bears N. 35° 16' E., 135.292 chs. dist., monumented with a steel reinforcement rod, 24 ins. long, ⅝ in. diam., firmly set flush with the surface of the ground. The geographic position, based on NAD83 (CORS96), is:</p> <p style="padding-left: 40px;">Latitude 42° 07' 27.5374" N., Longitude 96° 26' 37.8944" W. Height above ellipsoid (HAE), based on NAVD88, is: 417.75 meters.</p> <p>N. 89° 41' W., bet. secs. 25 and 36.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>19.755 Point for the E. 1/16 sec. cor. of secs. 25 and 36, at proportionate distance, falls in gravel surfaced road extending E. and W.; there is no remaining evidence of the original cor. Point not monumented.</p> <p>39.51 The 1/4 sec. cor. of secs. 25 and 36, monumented by person(s) unknown with an iron pipe, 22 ins. long, 1½ ins. diam., firmly set 12 ins. below gravel surfaced road extending E. and W., with an iron pipe, 24 ins. long, 1 in. diam., set alongside, bent at right angle in the middle, with a wood hub, 18 ins. long, 2 ins. square, and glass fragments buried alongside. This position is recorded in Surveyor's Record Book No. 1, p. 255, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p>
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E S 25 1/4— S 36 2011</p> <p>Deposit the 1½ in. iron pipe inside, and bury the wood and glass in a plastic bag alongside, the iron post. Remove the 1 in. diam. iron pipe from the vicinity.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 1¾° E., 48.1 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S25 31.8 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 6¾° E., 45.1 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S36 29.8 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located in projection of fence from the N., and 5 lks. W. of fence projection from the S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 51' W., beginning new measurement.</p> <p>Over rolling terrain, along gravel surfaced road.</p>
19.695	<p>The W. 1/16 sec. cor. of secs. 25 and 36, monumented by person(s) unknown with an angle iron, 32 ins. long, 1¼ ins. wide, firmly set 38 ins. below gravel surfaced road extending E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 30 ins. below the surface of the road, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E S 25 W 1/16—— S 36 2011</p> <p>Deposit the angle iron inside the iron post.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 21° E., 113.9 lks. dist., with brass cap mkd. RM T25N R8E W1/16 S25 75.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 1¼° W., 51.1 lks. dist., with brass cap mkd. RM T25N R8E W1/16 S36 33.7 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located in projection of fence from the S.</p> <p style="text-align: center;">_____</p> <p>N. 89° 50' W., beginning new measurement.</p> <p>Over rolling terrain, along gravel surfaced road.</p>
19.825	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p style="text-align: center;">_____</p> <p>From the cor. of secs. 13, 14, 23 and 24, monumented with an aluminum rod, ⅝ in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <p>N. 0° 19' E., bet. secs. 13 and 14.</p> <p>Over rolling terrain.</p>
19.94	<p>Point for the S. 1/16 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p> <p>39.88</p>	<p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 1/16 S 14 S 13 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located on SW. side of cor. post of abandoned fences extending E. and S., with evidence of older abandoned fence cor. lying loose in the vicinity.</p> <p>The 1/4 sec. cor. of secs. 13 and 14, monumented by person(s) unknown with an iron pipe, 29 ins. long, 1½ ins. diam., firmly set 30 ins. below the surface of cultivated field. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop the reset iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 14 S 13 2011</p> <p>Note: This position is depicted on a record filed in 1964 by Ziba N. Dewey, Nebraska Registered Land Surveyor No. 137, as recorded in Surveyor's Record Book No. 2, p. 211, in the Thurston County Courthouse. The retraced distance from this position to the center 1/4 sec. cor. of section 13, hereinafter described, is in harmony with corresponding distance shown on a right-of-way strip map, circa 1946, obtained from the Nebraska Dept. of Roads office in Lincoln, NE.</p> <p>Note: The position established in 1958 by A. Vinson Hiatt, Nebraska Deputy State Surveyor, as recorded in Surveyor's Record Book No. 2, p. 177, in the Thurston County Courthouse, was searched for, not recovered. Nevertheless, this position was based on erroneous control to the S., ignoring the nearby evidence, and is not accepted as the best available evidence of the original cor. position.</p> <hr style="width: 25%; margin-left: auto; margin-right: auto;"/>
----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p>N. 0° 14' W., beginning new measurement.</p> <p>Over gently rolling terrain, across cultivated field.</p> <p>2.95 Creek, drains W.</p> <p>20.052 Point for the N. 1/16 sec. cor. of secs. 13 and 14, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. Point not monumented.</p> <p>40.105 Point for the cor. of secs. 11, 12, 13 and 14, determined at intersection of subdivisional line from the W., projected through 200 ft. railroad right-of-way monument hereinafter described, and record distance from reference tie based on 1958 survey by A. Vinson Hiatt, Nebraska Deputy State Surveyor,</p> <p style="text-align: center;">The decayed lower portion of fence cor. post, bears S. 31° 12' E., 77.3 lks. dist. (Record: SE., 51.0 feet)</p> <p>There is no remaining evidence of the monument recovered in 1929 by H. B. Lawson, Nebraska Deputy State Surveyor. This method of restoration was determined to be the most applicable to reestablish the original cor. position. A detailed report describing this position is located in the official file for Group No. 175, NE.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a steel fence post, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="4">T25N R8E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 11</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 12</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 13</td> <td></td> </tr> <tr> <td colspan="4">2011</td> </tr> </table> </div> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. falls on steep slope of ditch on S. side of Nebraska State Highway No. 94, on N. side of drainage ditch, course W.</p> <p>from which</p> <p style="text-align: center;">A flat iron bar, bears S. 40¼° E., 80.3 lks. dist., ½ x 2 ins. wide, firmly set 60 ins. below the surface of the ground, of unknown origin and purpose.</p>	T25N R8E				S 11		S 12		S 14		S 13		2011			
T25N R8E																	
S 11		S 12															
S 14		S 13															
2011																	

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>An iron shaft, bears S. $31\frac{1}{4}^{\circ}$ E., 76.0 lks. dist., 1 in. square., firmly set 4 ins. below the surface of the ground, on N. side of decayed lower portion of fence cor. post, established in 1967 by R. H. Starman, Nebraska Dept. of Roads, as recorded in Surveyor's Record No. 2, p. 249.</p> <p>A steel reinforcement rod, bears S. $21\frac{3}{4}^{\circ}$ E., 106.8 lks. dist., $\frac{5}{8}$ in. diam., firmly set 6 ins. below the surface of the ground, with yellow plastic cap mkd. NEBRASKA DEPT. OF ROADS, set in 1993 by W. Hirely, Nebraska Dept. of Roads, as recorded on file obtained from Nebraska Dept. of Roads for Proj. No. BRS-94-7(103).</p> <p>A steel reinforcement rod, bears S. 15° E., 158.9 lks. dist., $\frac{5}{8}$ in. diam., firmly set 12 ins. below the surface of the ground in cultivated field, set in 1993 by Donovan D. Zager, Nebraska Registered Land Surveyor No. 269, as recorded in Plat Book No. 6, p. 53, in the Thurston County Courthouse.</p> <p>A steel reinforcement rod, bears S. $8\frac{1}{4}$ E., 308.0 lks. dist., $\frac{5}{8}$ in. diam., firmly set 12 ins. below the surface of the ground in cultivated field, set in 1993 by Donovan D. Zager, Nebraska Registered Land Surveyor No. 269, as recorded in Plat Book No. 6, p. 53, in the Thurston County Courthouse.</p> <p>A steel reinforcement rod, bears S. $48\frac{3}{4}^{\circ}$ W., 161.1 lks. dist., $\frac{5}{8}$ in. diam., firmly set 10 ins. below the surface of the ground, with yellow plastic cap mkd. NEBRASKA DEPT. OF ROADS, set in 1993 by W. Hirely, Nebraska Dept. of Roads, as recorded on file obtained from Nebraska Dept. of Roads for Proj. No. BRS-94-7(103).</p> <p>From this point, a position established in 1993 by Donovan D. Zager, Nebraska Registered Land Surveyor No. 269, bears S. $86^{\circ} 15'$ E., 45.6 lks. dist., monumented with an iron pipe, 24 ins. long, 1 in. diam., firmly set projecting 2 ins. above the ground, with steel reinforcement rod, $\frac{5}{8}$ in. diam., driven inside. This position is recorded on corner description for Nebraska Dept. of Roads Proj. No. 94-7(103), filed in Plat Book No. 6, p. 53, in the Thurston County Courthouse, and is not accepted as the best available evidence of the original cor. position. Note: The recovered iron pipe is out of record position (S. $79^{\circ} 52'$ E., 4.81 ft.) when compared to reference ties by</p>
----------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Mr. Zager and Mr. Hirely in 1993, to recovered steel reinforcement rods and iron bar.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 88° 57' W., bet. secs. 12 and 13.</p> <p>Over rolling terrain, along Nebraska State Highway No. 94.</p> <p>19.805 Point for the E. 1/16 sec. cor. of secs. 12 and 13, at proportionate distance, falls in asphalt surfaced road extending E. and W.; there is no remaining evidence of the original cor. This position is in harmony with a calculated position established by E. Gerald Erickson, Nebraska Registered Land Surveyor No. 107, as recorded in Plat Book No. 2, p. 60, in the Thurston County Courthouse.</p> <p>Set a steel nail survey marker, 4 ins. long, ⅜ in. diam., firmly set flush with the surface of road, inscribed SURVEY MARK, with a steel washer inscribed BLM CADASTRAL SURVEY and mkd. 2011.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 3¼° E., 72.8 lks. dist., with brass cap mkd. RM T25N R8E E1/16 S13 48.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 4¼° W., 153.8 lks. dist., with brass cap mkd. RM T25N R8E E1/16 S12 101.5 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located in E. bound lane of Nebraska State Highway No. 94.</p> <p>39.61 The 1/4 sec. cor. of secs. 12 and 13, monumented in 1966 by Leo Ridder, Nebraska State Dept. of Roads, with a steel reinforcement rod, ½ in. diam., firmly set 6 ins. below asphalt surfaced road extending E. and W., with an iron pipe, 6 ins. long, 1 in. diam., set over the top. This position is recorded</p>
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>in Surveyor's Record Book No. 2, p. 250, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position. Note: This position is attributed to a position reestablished in 1964 by Ziba N. Dewey, Nebraska Registered Land Surveyor No. 137, as recorded in Surveyor's Record Book No. 2, p. 211, in the Thurston County Courthouse. Point not remonumented.</p> <p>from which</p> <p>A right-of-way monument, bears S. 10° E., 120.0 lks. dist. measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the ground, plainly mkd. ROW on N. face.</p> <p>A right-of-way monument bears N. 1¾° W., 145.4 lks. dist. measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the ground, plainly mkd. ROW on S. face.</p> <hr/> <p>Note: The remainder of this line is provided for informational purposes only as the road intersection around the W. 1/16 sec. cor. position was not excavated due to safety concerns due to excessive traffic on Nebraska State Highways No. 77 and 94.</p> <p>N. 88° 56' W., beginning new measurement.</p> <p>Over rolling terrain, along Nebraska State Highway No. 94.</p> <p>19.00 N. bound lane of U.S. Highway No. 77, bears N. and S.</p> <p>19.45 S. bound lane of U.S. Highway No. 77, bears N. and S.</p> <p>20.085 The platted position for the W. 1/16 sec. cor. of secs. 12 and 13, as recorded on right-of-way strip map for Project FAS 373 (2), obtained from the Nebraska Dept. of Roads, date unknown, falls on projection of W. right-of-way of U.S. Highway No. 77 from the N., on W. side of intersection with Nebraska State Highway No. 94 extending E. and W. This position was not excavated due to safety concerns due to excessive truck traffic. The platted position is accepted as the best available evidence of the original cor. position until such time that a careful search can be coordinated with the Nebraska Dept. of Roads.</p>
----------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Note: This position is also in harmony with the proportionate position if calculated using the overall distance of the mile between secs. 12 and 13.</p> <hr/> <p>N. 88° 56' W., beginning new measurement.</p> <p>Over rolling terrain, gradually leaving the asphalt surface of Nebraska State Highway No. 94.</p> <p>19.905 The cor. of secs. 11, 12, 13 and 14.</p> <hr/> <p>N. 0° 08' W., bet. secs. 11 and 12.</p> <p>Over rolling terrain.</p> <p>0.75 Nebraska State Highway No. 94, bears E. and W.</p> <p>20.01 Point for the S. 1/16 sec. cor. of secs. 11 and 12, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 1/16 S 11 S 12 2011</p> <p>Note: A steel reinforcement rod, 18 ins. long, 5/8 in. diam., with washer welded to one end and a nut and washer welded to opposite end, was found lying loose on the surface of the ground nearby. Deposited steel reinforcement rod inside the iron pipe.</p> <p>Cor. is located N. 5¼° W., 2.71 chs. dist., from cor. of fences extending S. and WNW.</p> <p>40.02 The 1/4 sec. cor. of secs. 11 and 12, monumented in 1913 by Wilbur A. Racely, Thurston County Surveyor, with an iron pipe, 39 ins. long, 2 ins. diam., firmly set 14 ins. below the surface of cultivated field, with an iron pipe, 1 in. diam., driven inside, with crockery and brick fragments buried alongside. This position is recorded in Official Record of Survey Book No. 3, p. 7, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p>
----------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop the reset iron pipes, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 11 S 12 2011</p> <p>Bury the crockery and brick fragments in a plastic bag alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 08' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.935	<p>Point for the N. 1/16 sec. cor. of secs. 11 and 12, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E N 1/16 S 11 S 12 2011</p>
26.80	Omaha Creek, drains NNE.
39.87	<p>The cor. of secs. 1, 2, 11 and 12, attributed to Wilbur A. Racely, Thurston County Surveyor, monumented with an iron pipe, 1¼ ins. diam., firmly set 36 ins. below the surface of cultivated field, with glass fragments buried alongside. This position is recorded in Surveyor's Record Book No. 1, pgs. 226 and 235, and Official Record of Survey Book No. 3, pgs. 7 and 33, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop the iron pipe, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains									
	<div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T25N R8E</td> </tr> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td>S 11</td> <td>S 12</td> </tr> <tr> <td colspan="2">2011</td> </tr> </table> </div> <p>Bury the glass fragments in plastic bag alongside the iron post.</p> <p>From this point, a monument recovered in 1992 by William H. Heileman, Nebraska Registered Land Surveyor No. 386, bears N. 1° 02' E., 22.7 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set 10 ins. below the surface of the ground, on E. edge of cultivated field. This position is recorded in Plat Book No. 6, p. 36, in the Thurston County Courthouse, and is not accepted as the best available evidence of the original cor. position.</p> <p>From this same point, a monument established by person(s) unknown, bears S. 88° 37' W., 38.9 lks. dist., monumented with an iron pipe, 44 ins. long, 1¼ ins. diam., firmly set 10 ins. below the surface of cultivated field with threaded insert on bottom end. This position is not accepted as the best available evidence of the original cor. position. Reset the iron pipe in place, 24 ins. below the surface of the ground.</p> <p>Cor. is located 3.35 chs. E. of center of railroad track, bears NNE. and SSW.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 88° 55' W., bet. secs. 1 and 12.</p> <p>Over rolling terrain, along dirt surfaced road.</p> <p>20.005 Point for the E. 1/16 sec. cor. of secs. 1 and 12, at proportionate distance, falls in dirt surfaced road extending E. and W.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p>	T25N R8E		S 2	S 1	S 11	S 12	2011	
T25N R8E									
S 2	S 1								
S 11	S 12								
2011									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E S 1 E 1/16—— S 12 2011</p>
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 1° W., 42.1 lks. dist., with brass cap mkd. RM T25N R8E E1/16 S12 27.8 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 2½° W., 59.6 lks. dist., with brass cap mkd. RM T25N R8E E1/16 S1 39.3 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located 3 lks. E. of projection of fences from the N. and S.</p>
32.00	Road gradually turns to gravel surfaced.
40.01	<p>The 1/4 sec. cor. of secs. 1 and 12, perpetuated during a survey attributed to E. C. Simmons, Thurston County Surveyor, monumented with a granite stone, 13x8x7 ins., no mks. visible, with an iron pipe, 36 ins. long, 1 in. diam., a steel reinforcement rod, 12 ins. long, 3/8 in. diam., a solid iron axle, 49 ins. long, 1 in. diam., and glass fragments alongside, all firmly set 12 ins. below gravel surfaced road extending E. and W., in projection of gravel surfaced driveway extending NNE. This position is recorded in Official Record of Survey Book No. 3, p. 33, in the Thurston County Courthouse, and is accepted as a careful and faithful perpetuation of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E S 1 1/4—— S 12 2011</p>
	<p>Deposit the iron pipe and solid iron axle inside, and bury the unmkd. stone and glass fragments in a plastic bag alongside, the iron post.</p>
	<p>from which</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 47° E., 75.6 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S1 49.9 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 31° E., 51.5 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S12 34.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 88° 43' W., beginning new measurement.</p>
	<p>Over rolling terrain, along gravel surfaced road.</p>
19.36	<p>U.S. Highway No. 77, bears SSE. and NNW.</p>
19.89	<p>The W. 1/16 sec. cor. of secs. 1 and 12, monumented in 1967 by R. H. Starman, Nebraska State Dept. of Roads, with a solid iron rod, 25 ins. long, 1 in. square, firmly set 10 ins. below the surface of the ground on W. shoulder of U.S. Highway No. 77, in projection of gravel surfaced road from the E. and field access road from the W.. This position is recorded in Surveyor's Record Book No. 2, p. 249, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position. Note: This position is attributed to a position reestablished in 1964 by Ziba N. Dewey, Nebraska Registered Land Surveyor No. 137, as recorded in Surveyor's Record Book No. 2, p. 211, in the Thurston County Courthouse.</p>
	<p>At the corner point</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 1 W 1/16— S 12 2011</p> <p>Deposit the square iron rod inside the iron post.</p> <hr/> <p>N. 89° 04' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>18.70 Omaha Creek, drains NNW.</p> <p>19.865 The cor. of secs. 1, 2, 11 and 12.</p> <hr/> <p>N. 0° 17' W., bet. secs. 1 and 2.</p> <p>Over rolling terrain.</p> <p>3.80 Omaha Creek, drains NW.</p> <p>14.65 Center of railroad track, bears NNE. and SSW.</p> <p>19.625 Point for the S. 1/16 sec. cor. of secs. 1 and 2, at proportionate distance, falls on edge of cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 1/16 S 2 S 1 2011</p> <p>Cor. is located 1.14 chs. W. of center of railroad track, bears NNE. and SSW., and 1.8 chs. E. of Omaha Creek, drains N.</p> <p>30.00 Omaha Creek, drains N.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
39.25	<p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate distance, falls in E. ditch of gravel surfaced road extending N. and SSW. on slight curve; there is no remaining evidence of the original cor. Note: This position is in harmony with a survey attributed to E. C. Simmons, Thurston County Surveyor, as recorded in Official Record of Survey Book No. 3, p. 33, in the Thurston County Courthouse.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 2 S 1 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 12 lks. S. of projection of fence from the W., in overall projection of fence from the E.</p> <p>From this point, a position established by person(s) unknown, bears N. 8° 21' E., 10.8 lks. dist., monumented with a steel reinforcement rod, ¼ in. diam., firmly set flush with the surface of the ground. This position appears to be established utilizing erroneous controlling cor. to the S., and is not accepted as the best available evidence of the original cor. position.</p> <p>Thence continue along gravel surfaced road.</p>
58.875	<p>Point for the N. 1/16 sec. cor. of secs. 1 and 2, at proportionate distance, falls in gravel surfaced road extending N. and S.; there is no remaining evidence of the original cor. Point not monumented.</p>
78.265	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2002-03 dependent resurvey of T. 26 N., R. 8 E.</p> <hr/> <p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 0° 04' E., bet. secs. 34 and 35.</p> <p>Over rolling terrain.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
20.04	Point for the S. 1/16 sec. cor. of secs. 34 and 35, at proportionate distance, falls in gravel surfaced road extending NNE. and SSW.; there is no remaining evidence of the original cor. Point not monumented.
36.55	Center of railroad track, bears NNE. and SSW.
40.08	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance, falls in field access trail extending NNE. and SSW.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 34 S 35 2011</p> <p>Note: While excavating in area, recovered numerous fragments of vitrified clay tile, some with the flared bell portion evident, remnants of the monument set in 1914 by Wilbur A. Racely, Thurston County Surveyor, as recorded in Official Record of Survey Book No. 3, p.11, in the Thurston County Courthouse. Buried the clay tile fragments in a plastic bag alongside the iron post.</p> <p>Cor. is located 95 lks. W. of center of railroad track, bears NNE. and SSW.</p>
60.12	<p>Point for the N. 1/16 sec. cor. of secs. 34 and 35, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E N 1/16 S 34 S 35 2011</p>
80.16	The cor. of secs. 26, 27, 34 and 35, monumented by person(s) unknown with the lower bell portion of a vitrified clay tile, 18 ins. long, 4 ins. diam., firmly set flush with surface of dirt road extending E. and W. This position is recorded in Surveyor's Record Book No. 1, pgs. 253-254, in the Thurston

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, inside the vitrified clay tile, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T25N R8E</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> <tr> <td colspan="2">2011</td> </tr> </table> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 2¾° E., 38.2 lks. dist., with brass cap mkd. RM T25N R8E S26 25.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 2¾° W., 33.4 lks. dist., with brass cap mkd. RM T25N R8E S34 22.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>From this point, a position monumented by person(s) unknown, bears N. 29° 17' W., 43.4 lks. dist., with a steel reinforcement rod, 12 ins. long, ¾ in. diam., firmly set 2 ins. below the surface of the ground, alongside cor. post of fence extending N. and N. right-of-way fence extending W. This position is not accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89° 53' W., bet. secs. 26 and 35.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>19.95 Projection of fence from the N.</p>	T25N R8E		S 27	S 26	S 34	S 35	2011	
T25N R8E									
S 27	S 26								
S 34	S 35								
2011									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
20.197	Point for the E. 1/16 sec. cor. of secs. 26 and 35, at proportionate distance, falls in gravel surfaced road extending E. and W.; there is no remaining evidence of the original cor. Point not monumented.
35.70	Leave gravel surfaced road, bears E. and WNW., on slight curve.
40.395	Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance, falls on S. edge of drainage ditch, course NW.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a steel fence post, with brass cap mkd.
	T25N R8E S 26 1/4—— S 35 2011
	Set a fiberglass sign post alongside the iron post.
	From this point, a position established in 1990 by Clyde R. Flowers, Jr., Nebraska Registered Land Surveyor No. 357, as shown on a record obtained from the Nebraska State Surveyor's Office, was searched for, not recovered. Nevertheless, this position was established utilizing erroneous control to the W. and is not accepted as a careful and faithful reestablishment of the original cor. position.
	Cor. is located S. 48½° E., 56 lks. dist., from SE. edge of large diam. drainage culvert under road.
47.35	Enter gravel surfaced road, bears ENE. and W.
57.00	Leave gravel surfaced road, bears E. and WSW., at point crossing creek, drains NNW.
60.593	Point for the W. 1/16 sec. cor. of secs. 26 and 35, at proportionate distance, falls in N. ditch of gravel surfaced road extending ENE. and WSW.; there is no remaining evidence of the original cor. Point not monumented.
67.00	Gravel surfaced road, bears NNE. and SSW.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
69.00	Center of railroad track, bears NNE. and SSW.
80.79	The cor. of secs. 26, 27, 34 and 35. <hr style="width: 50%; margin-left: 0;"/> N. 0° 07' E., bet. secs. 26 and 27. Over rolling terrain.
20.06	Point for the S. 1/16 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd. <div style="text-align: center;"> T25N R8E S 1/16 S 27 S 26 2011 </div> Set a fiberglass sign post alongside the iron post. Cor. falls in abandoned fence extending N. and S., 1.65 chs. S. of projection of divide between cultivated fields from the E.
40.12	The 1/4 sec. cor. of secs. 26 and 27, monumented by person(s) unknown with a flat iron bar, 34 ins. long, 1½ ins. wide, firmly set 4 ins. below the surface of the ground, upper 4 ins. bent towards the W., with glass fragments around base. This position is accepted as the best available evidence of the original cor. position. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd. <div style="text-align: center;"> T25N R8E 1/4 S 27 S 26 2011 </div> Deposit the inverted iron bar inside, and bury the glass fragments in a plastic bag and set a fiberglass sign post alongside, the iron post.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>Cor. is located S. $12\frac{1}{4}^\circ$ E., 1.5 lks. dist., from intersection of abandoned fences extending E., S. and W., and N. 89° W., 47 lks. dist., from intersection of abandoned fences extending N., E. and W.</p> <hr/>
	<p>From the cor. of secs. 13, 14, 23 and 24, monumented with an aluminum rod, $\frac{5}{8}$ in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E.</p>
	<p>S. $89^\circ 40'$ W., between secs. 14 and 23.</p>
	<p>Over nearly level terrain, along abandoned road.</p>
16.90	<p>Center of railroad track, bears NNE. and SSW.</p>
18.30	<p>Road, gravel surfaced, bears NNE. and SSW.</p>
19.88	<p>Point for the E. $\frac{1}{16}$ sec. cor. of secs. 14 and 23, at proportionate distance, falls on edge of cultivated field; there is no remaining evidence of the original cor. Point not monumented.</p>
39.76	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R8E S 14 $\frac{1}{4}$—— S 23 2012</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
	<p>From this point, the monument established in 1929 by H. B. Lawson, and the reference monuments established in 1958 by A. V. Hiatt, were searched for, not found. Nevertheless, this position was established based on erroneous control to the E. and is not accepted as a careful and faithful reestablishment of the original cor. position.</p>
	<p>Cor. is located S. $84\frac{1}{2}^\circ$ E., 9.3 lks. dist., from intersection of fences extending N., E. and W.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
59.64	<p>Point for the W. 1/16 sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E S 14 W 1/16— S 23 2012</p> </div> <p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, the position established in 1929 by H. B. Lawson, Deputy State Surveyor, bears S. 60° 15' W., 10.2 lks. dist., monumented with an iron pipe, 1½ ins. diam., firmly set 12 ins. below the surface of cultivated field, from which the angle iron reference monuments established in 1958 by A. Vinson Hiatt, Deputy State Surveyor,</p> <p style="padding-left: 40px;">An angle iron, 2 ins. wide, bears N. 85° 16' E., 55.4 lks. dist., firmly set projecting 2 ins. above the ground, in fence extending E. and W.</p> <p style="padding-left: 40px;">An angle iron, 2 ins. wide, bears N. 82° 38' W., 44.6 lks. dist., firmly set flush with the surface of the ground, in fence extending E. and W.</p> <p>This position is recorded in the Thurston County Courthouse, was established based on erroneous control to the E., and is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located S. 72¼° E., 3.7 lks. dist., from intersection of fences extending N., E. and W.</p>
70.70	Nebraska State Highway No. 94, bears NE. and SW.
79.52	<p>The cor. of secs. 14, 15, 22 and 23, monumented by person(s) unknown with lower bell portion of vitrified clay tile, 10 ins. long, 4 ins. diam., fractured but firmly set flush with dirt surfaced road extending N. and S., with segment of steel fence post, 18 ins. long, driven in the center, with a solid iron shaft, 31 ins. long, 1 in. diam., set alongside, perpetuated in 1929 by H. B. Lawson,</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Deputy State Surveyor, with a paving brick plainly mkd. HL 29 buried alongside. This position is recorded in Surveyor's Record Book No. 2, p. 153, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T25N R8E</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td colspan="2">2011</td> </tr> </table> </div> <p>Deposit the solid iron shaft inside, and bury the tile fragments and brick in plastic bags alongside, the iron post. Remove the steel fence post segment from the vicinity.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 88° E., 71.6 lks. dist., with brass cap mkd. RM T25N R8E S14 47.3 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 87½° W., 36.9 lks. dist., with brass cap mkd. RM T25N R8E S15 24.4 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr/> <p>N. 0° 06' E., bet. secs. 14 and 15.</p> <p>Over rolling terrain, along dirt surfaced road.</p> <p>19.99 Point for the S. 1/16 sec. cor. of secs. 14 and 15, at proportionate distance, falls on W. edge of slight bend in dirt surfaced road extending N. and S.; there is no remaining evidence of the original cor.</p>	T25N R8E		S 15	S 14	S 22	S 23	2011	
T25N R8E									
S 15	S 14								
S 22	S 23								
2011									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 1/16 S 15 S 14 2011</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 88¾° E., 48.7 lks. dist., with brass cap mkd. RM T25N R8E S1/16 S14 32.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 89¾° W., 30.5 lks. dist., with brass cap mkd. RM T25N R8E S1/16 S15 20.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>From this point, a position established by person(s) unknown, bears N. 81° 54' E., 13.1 lks. dist., monumented with a steel reinforcement rod, ⅝ in. diam., firmly set flush with the surface of the road, with remains of a red plastic cap on the top. This position is of unknown origin, is not in harmony with the 1929 H. B. Lawson survey plat or the readily identifiable monumentation to the N. and S., and is not accepted as the best available evidence of the original cor. position.</p>
39.98	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set fiberglass sign posts alongside the 1993 reference monuments.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89° 12' W., bet. secs. 11 and 14.</p> <p>Over rolling terrain.</p>
4.50	<p>Omaha Creek, drains N.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
9.18	Railroad right-of-way monument, an iron bolt, 1 in. diam. with nut on top, 2 ins. square, firmly set 24 ins. below the surface of the ground, at 200 ft. offset as depicted on railroad plat dated May 13, 1926, obtained from the Nebraska Dept. of Roads. This position is depicted as being set on the subdivisional line between secs. 11 and 14, and is utilized for alignment of this line during the course of this resurvey.
10.695	Platted position of railroad right-of-way monument, at 100 ft. offset, was searched for, not recovered.
12.205	Center of railroad track, bears NNE. and SSW.
14.20	Nebraska State Highway No. 94, bears N. and S.; thence along alleyway in Walthill, NE.
19.85	<p>The E. 1/16 sec. cor. of secs. 11 and 14, at intersection of center lines of Tallman Street extending N. and S., and alleyway extending E. and W. This position is depicted in a field tablet record of surveys attributed to Charles M. Finley as obtained from MLS and Associates, P.L.C. (formerly Schieuer Surveying, P.C.), in Sioux City, Iowa, is in harmony with 1906 Plat of Walthill by Hamet R. Case, and is accepted as the best available evidence of the original cor. position. Point not monumented.</p> <hr/> <p>S. 89° 12' W., beginning new measurement.</p> <p>Over nearly level terrain, along alleyway.</p>
9.965	A position established in 1977 for the W-E 1/64 sec. cor. of secs. 11 and 14, by E. Gerald Erickson, Nebraska Registered Land Surveyor No. 107, an "X" chiseled in alleyway concrete paving with concrete nail driven in center, bears SOUTH, 1.4 lks. dist.
19.895	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set a fiberglass sign post alongside the iron post.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 2 and 3, monumented by person(s) unknown with an iron pipe, 19 ins. long, 2 ins. diam., firmly set flush with the surface of the ground, with glass fragments around base. This position is recorded in Official Record of Survey Book No. 3, p. 57, in the Thurston</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 1/16 S 3 S 2 2011</p> <p>Bury the iron pipe, and the glass fragments in a plastic bag, and set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 67¾° E., 17.2 lks. dist., from decayed cor. post of abandoned fences extending N., S. and W.</p> <p>N. 0° 49' W., bet. secs. 2 and 3.</p> <p>Over rolling terrain.</p> <p>Note: There appears to be a platting or calculation error concerning the distances on this line shown on the record in Official Record of Survey Book No. 3, p 57. If viewed closely, the correct proportionate distances have been over written with incorrectly calculated distances. Because of this apparent confusion and the lack of recovery of any further local monumentation, proportionate measurements along this line during this resurvey are based upon the official plat and not the county survey record.</p>
19.00	Toe of hill; thence across nearly level flood plain of small creek bottom.
19.975	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor. or the cor. recorded in the Thurston County Courthouse.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a steel fence post, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E 1/4 S 3 S 2 2011</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
23.00	<p>Creek, drains E.; thence across rolling terrain.</p>
39.95	<p>Point for the N. 1/16 sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original cor. or the cor. recorded in the Thurston County Courthouse. Point not monumented.</p>
59.685	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2002-03 dependent resurvey of T. 26 N., R. 8 E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22, monumented by person(s) unknown with a vitrified clay tile, 4 ins. diam., firmly set 36 ins. below W. lane of gravel surfaced road extending N. and S., with a solid iron shaft, 1 in. diam., driven in the center. This position is recorded in Surveyor's Record Book No. 1, p. 242, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the surface of the road, atop the vitrified clay tile and solid iron axle, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 21 S 22 2011</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 88¾° E., 54.4 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S22 35.9 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 89¼° W., 48.0 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S21 31.7 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located in projection of fences from the E. and W.</p> <p>N. 0° 42' E., bet. secs. 21 and 22.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>19.87 Point for the N. 1/16 sec. cor. of secs. 21 and 22, at proportionate distance, falls in gravel surfaced road extending N. and S.; there is no remaining evidence of the original cor. Point not monumented.</p> <p>39.74 The cor. of secs. 15, 16, 21 and 22, monumented by person(s) unknown with the lower bell portion of a vitrified clay tile, 12 ins. long, 4 ins. diam., firmly set 24 ins. below gravel surfaced road extending N. and S. This position is recorded in Surveyor's Record Book No. 1, pgs. 238 and 242, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, inside the vitrified clay tile, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T25N R8E</td> </tr> <tr> <td>S 16</td> <td>S 15</td> </tr> <tr> <td>S 21</td> <td>S 22</td> </tr> <tr> <td colspan="2">2011</td> </tr> </table> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 70¼° E., 56.6 lks. dist., with brass cap mkd. RM T25N R8E S22 37.4 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>	T25N R8E		S 16	S 15	S 21	S 22	2011	
T25N R8E									
S 16	S 15								
S 21	S 22								
2011									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears WEST, 45.6 lks. dist., with brass cap mkd. RM T25N R8E S21 30.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>From this point, a position established by person(s) unknown, bears N. 0° 37' W., 41.9 lks. dist., monumented with a solid iron axle, 48 ins. long, 1 in. diam., firmly set 16 ins. below gravel surfaced road extending N. and S., upper 12 ins. bent toward the S. This position's description was recorded in Surveyor's Record Book No. 1, p. 238, but was crossed out and replaced with the description of the vitrified clay tile. The surrounding local evidence suggests that the vitrified clay tile has been the locally accepted cor. position, and therefore the iron axle is not accepted as the best available evidence of the original cor. position. I straighten the iron axle and drive in place, 24 ins. below the surface of the road.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89° 58' W., bet. secs. 15 and 22.</p> <p>Over rolling terrain, along overgrown abandoned road.</p>
20.055	<p>Point for the E. 1/16 sec. cor. of secs. 15 and 22, at proportionate distance, falls in abandoned road extending E. and W.; there is no remaining evidence of the original cor. Point not monumented.</p>
40.11	<p>Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance based on a field tablet record of surveys attributed to Charles M. Finley as obtained from MLS and Associates, P.L.C. (formerly Schieuer Surveying, P.C.), in Sioux City, Iowa; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 15 1/4—— S 22 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Cor. is located N. 12½° W., 42 lks. dist., of power pole utilized as cor. of abandoned fences extending N. and E.</p> <hr/> <p>N. 89° 58' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>20.11 Point for the W. 1/16 sec. cor. of secs. 15 and 22, at proportionate distance, falls 52 lks. N. of fence extending E. and W.; there is no remaining evidence of the original cor. Point not monumented.</p> <p>40.22 The cor. of secs. 15, 16, 21 and 22.</p> <hr/> <p>(Restoring the dependent resurvey executed by Richard A. Kohler in 1993)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set a fiberglass sign post alongside the iron post.</p> <p>N. 0° 29' W., between secs. 3 and 4.</p> <p>Over rolling terrain.</p> <p>19.97 Point for the N. 1/16 sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E N 1/16 S 4 S 3 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 62½° W., 1.7 lks. dist., from cor. post of abandoned fences extending N. and E.</p>
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
39.08	<p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an aluminum rod, $\frac{5}{8}$ in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented by person(s) unknown with an iron pipe, 29 ins. long, $1\frac{3}{4}$ ins. diam., firmly set 33 ins. below gravel surfaced road extending N. and S., perpetuated by Fred M. Franklin, Nebraska Registered Land Surveyor No. 525, with a steel reinforcement rod, 24 ins. long, $\frac{5}{8}$ in. diam., set over the top, with aluminum cap mkd. COUNTY SURVEYOR FRED M. FRANKLIN LS525. This position is recorded in Plat Book No. 8, p. 117, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E 1/4 S 32 S 33 2011</p> </div> <p>Deposit the iron pipe and steel reinforcement rod inside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground for a reference monument, bears N. $87\frac{3}{4}^\circ$ E., 51.5 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S33 34.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground for a reference monument, bears N. $86\frac{1}{4}^\circ$ W., 50.0 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S32 33.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p> <p>20.04</p> <p>40.08</p>	<p>N. 0° 02' W., bet. secs. 32 and 33.</p> <p>Over rolling terrain, along gravel surfaced road.</p> <p>Point for the N. 1/16 sec. cor. of secs. 32 and 33, at proportionate distance, falls in gravel surfaced road extending N. and S.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E N 1/16 S 32 S 33 2011</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 49° E., 68.9 lks. dist., with brass cap mkd. RM T25N R8E N1/16 S33 45.4 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 84¾° W., 48.6 lks. dist., with brass cap mkd. RM T25N R8E N1/16 S32 32.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located 5 lks. S. of projection of fence from the W.</p> <p>The cor. of secs. 28, 29, 32 and 33, monumented by person(s) unknown with a solid iron rod, 1 in. diam., firmly set 63 ins. below the intersection of gravel surfaced roads extending N., E. and S. with dirt surfaced road extending W., atop of which was set an angle iron, 46 ins. long, 2 ins. wide, atop of which was set a steel reinforcement rod, 24 ins. long, ½ in. diam., with glass fragments buried alongside. This position is recorded in Surveyor's Record Book No. 1, p. 250, in the Thurston County Courthouse and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p>
------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins. below the surface of the roads, atop the solid iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td colspan="2">T25N R8E</td> </tr> <tr> <td>S 29</td> <td> S 28</td> </tr> <tr> <td>S 32</td> <td> S 33</td> </tr> <tr> <td colspan="2">2011</td> </tr> </table> </div> <p>Bury the glass fragments in a plastic bag alongside the iron post. Remove the angle iron and steel reinforcement rod from the vicinity.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 43½° E., 73.8 lks. dist., with brass cap mkd. RM T25N R8E S28 48.7 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 41° E., 75.7 lks. dist., with brass cap mkd. RM T25N R8E S33 49.9 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34, monumented by person(s) unknown with an iron pipe, 3 ins. diam., firmly set 64 ins. below the surface of field access driveway, with an iron pipe, 1½ ins. square, driven into the center, with two unmkd. granite stones and glass and paving brick fragments alongside, and with an iron pipe, 36 ins. long, 1½ ins. diam., with a steel reinforcement rod, 30 ins. long, ⅝ in. diam., driven in the center, set alongside to the E. This position is recorded in Surveyor's Record Book No. 1, p. 248, in the Thurston County Courthouse and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop the lower pipe with square iron pipe driven in the center, with brass cap mkd.</p>	T25N R8E		S 29	S 28	S 32	S 33	2011	
T25N R8E									
S 29	S 28								
S 32	S 33								
2011									

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E $\frac{S\ 28}{S\ 33} \mid \frac{S\ 27}{S\ 34}$ 2011</p> <p>Bury the paving brick and glass fragments in a plastic bag, the unmkd. stones and set a fiberglass sign post alongside the iron post. Remove the 1½ in. diam. iron pipe and the steel reinforcement rod from the vicinity.</p> <p>Cor. is located in projection of dirt surfaced roads from the E. and S.</p> <p>N. 89° 56' W., bet. secs. 28 and 33.</p> <p>Over rolling terrain.</p>
19.85	<p>Point for the E. 1/16 sec. cor. of secs. 28 and 33, at proportionate distance, falls S. 62° E, 24 lks. dist., from intersection of fences extending N., E. and S.; there is no remaining evidence of the original cor. Point not monumented.</p>
39.70	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 28 1/4 ——— S 33 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 19 lks. E. of fence extending N. and S.</p>
46.70	<p>Enter dirt surfaced field access road, bears NE. and W.</p>
59.55	<p>Point for the W. 1/16 sec. cor. of secs. 28 and 33, at proportionate distance, falls in dirt surfaced field access road extending E. and W.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E S 28 W 1/16—— S 33 2011</p> <p>Cor. is located 14 lks. W. of projection of fence from the N.</p> <p>From this point, a position established in 1978 by Frank J. Bohac, Nebraska Registered Land Surveyor No. 43, as recorded in Plat Book No. 3, p. 16., was searched for, not recovered. This position was concluded to represent a parcel cor. of a 40 acre parcel in sec. 28, and was not intended to represent the W. 1/16 sec. cor. position, and is therefore not utilized during the course of this resurvey.</p>
79.40	<p>The cor. of secs. 28, 29, 32 and 33.</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89° 54' W., bet. secs. 16 and 21.</p> <p>Over rolling terrain.</p>
19.99	<p>Point for the E. 1/16 sec. cor. of secs. 16 and 21, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E S 16 E 1/16—— S 21 2011</p> <p>Cor. is located N. 21° E., 21 lks. dist., from cor. post of abandoned fences extending E., S. and W., and N. 17½° E., 24 lks. dist., from cor. post of recently constructed fences extending E. and S.</p>
39.98	<p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance, falls N. 17¼° E., 31 lks. dist., from projected cor. of abandoned fences from the N. and E., there is no remaining evidence of the original cor. Point not monumented.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
59.97	Point for the W. 1/16 sec. cor. of secs. 16 and 21, at proportionate distance, falls N. 85° W., 20 lks. dist., from intersection of fences extending N., E. and W. on S. side of field access road; there is no remaining evidence of the original cor. Point not monumented.
79.96	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 2008 dependent resurvey of a portion of T. 25 N., R. 8 E.
	<hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by Richard A. Kohler in 1993)</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set a fiberglass sign post alongside the iron post.</p> <p>N. 0° 27' W., between secs. 4 and 5.</p> <p>Over rolling terrain.</p>
19.925	<p>Point for the N. 1/16 sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E N 1/16 S 5 S 4 2011</p>
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. falls 1 lk. W. of fence extending N. and S.</p>
39.96	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an aluminum rod, ⅜ in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 26 N., R. 8 E. Set fiberglass sign posts alongside the 1993 reference monuments.</p> <hr/>

Dependent Resurvey, Subdivision of Section 1,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 1 and 12.</p>
	<p>N. 0° 03' W., on the N. and S. center line of sec. 1.</p>
	<p>Over rolling terrain, along gravel surfaced driveway.</p>
18.00	<p>Leave gravel surfaced driveway on curve, bears NE. and S.; thence along dirt surfaced field access road.</p>
19.765	<p>Point for the center S. 1/16 sec. cor. of sec. 1, at proportionate distance, falls in W. ditch of dirt surfaced field access road extending N. and S.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 12 ins. long, 2½ ins. diam., 12 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
	<p>T25N R8E C S 1/16 S 1 C 2011</p>
	<p>Set a fiberglass sign post alongside the iron post.</p>
	<p>Cor. is located 19 lks. N. of projection of fence from the W., and 25 lks. N. of projection of fence from the E.</p>
	<p>From this point, a position established in 2005 by Fred M. Franklin, Nebraska Registered Land Surveyor No. 525, bears S. 3° 10' W., 1.8 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set 10 ins. below the surface of the ground, with red plastic cap mkd. FRANKLIN RLS 525, with a steel fence post alongside, as recorded in Plat Book No. 10, p. 7, in the Thurston County Courthouse. This position was established from erroneous control to the N. and is not accepted as a careful and faithful reestablishment of the original cor. position.</p>
39.53	<p>The center 1/4 sec. cor. of sec. 1, monumented by person(s) unknown with an iron pipe, 24 ins. long, 1¼ ins. diam., firmly set 22 ins. below the surface of the ground, with glass fragments around base, located 2 lks. N. of cor. post of</p>

Dependent Resurvey, Subdivision of Section 1,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>fences extending S., W. and abandoned E. This position is recorded in Official Record of Survey Book No. 3, p. 33, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C 1/4 S 1 2011</p> <p>Deposit the iron pipe inside, and bury the glass fragments in a plastic bag and set a fiberglass sign post alongside, the iron post.</p> <p>From this point, a position established by person(s) unknown, bears S. 2° 36' W., 3.6 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set flush with the surface of the ground. This position was utilized in 2005 by Fred M. Franklin, Nebraska Registered Land Surveyor No. 525, as recorded in Plat Book No. 10, p. 7, in the Thurston County Courthouse, and is not accepted as the best available evidence of the original cor. position.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 89° 29' W., on the E. and W. center line of sec. 1.</p> <p>Over rolling terrain.</p> <p>20.02 Point for the center E. 1/16 sec. cor. of sec. 1, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
----------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 1,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p style="text-align: center;">T25N R8E E 1/16 C ——— C S 1 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 37 lks. S. of fences extending irregularly E. and W.</p> <p>40.04 The center 1/4 sec. cor. of sec. 1.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. 89° 22' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>19.955 The center W. 1/16 sec. cor. of sec. 1, monumented in 1967 by R. H. Starman, Nebraska State Dept. of Roads, with a steel reinforcement rod, 26 ins. long, 1 in. diam., firmly set 8 ins. below E. ditch of U.S. Highway No. 77 extending SSE. and NNW. This position is recorded in Surveyor's Record Book No. 2, p. 249, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. below the surface of the ground, atop the steel reinforcement rod driven in place, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E W 1/16 C ——— C S 1 2011</p> <p>from which</p> <p style="padding-left: 40px;">A right-of-way monument, bears S. 89¾° E., 80.6 lks. dist., measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the surface of the ground, plainly mkd. ROW on W. face.</p>
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 1,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>A right-of-way monument, bears N. $88\frac{3}{4}^{\circ}$ W., 208.4 lks. dist., measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the surface of the ground, plainly mkd. ROW on E. face.</p> <p>Cor. is located 2.08 chs. E. of center line saw joint of U.S. Highway No. 77, bears SSE. and NNW.</p> <hr/> <p>N. $89^{\circ} 15'$ W., beginning new measurement.</p> <p>Over rolling terrain.</p>
13.405	Center of railroad track, bears NNE. and SSW.
19.955	The 1/4 sec. cor. of secs. 1 and 2.
	<hr/> <p style="text-align: center;">Subdivision of Section 1, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the E. 1/16 sec. cor. of secs. 1 and 12.</p> <p>N. $0^{\circ} 01'$ W., on the N. and S. center line of the SE$\frac{1}{4}$ of sec. 1.</p> <p>Over rolling terrain.</p>
19.865	<p>Point for the SE. 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E SE 1/16 S 1 2011</p> <p>Cor. is located N. $29\frac{3}{4}^{\circ}$ E., 21 lks. dist., from intersection of fences extending E., S. and W.</p>

Subdivision of Section 1,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
39.73	<p>The center E. 1/16 sec. cor. of sec. 1.</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 89° 12' W., on the E. and W. center line of the SE¼ of sec. 1.</p> <p>Over rolling terrain.</p>
20.01	The SE. 1/16 sec. cor. of sec. 1.
40.02	<p>The center S. 1/16 sec. cor. of sec. 1.</p> <hr/> <p>From the W. 1/16 sec. cor. of sec. 1 and 12.</p> <p>N. 0° 10' W., on the N. and S. center line of the SW¼ of sec. 1.</p> <p>Over rolling terrain, along U.S. Highway No. 77 right-of-way.</p>
19.635	<p>Point for the SW. 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the SW¼, falls on asphalt surface of U.S. Highway No. 77, bears SSE. and NNW.</p> <p>Set a steel nail survey marker, 4 ins. long, ⅜ in. diam., set flush with the surface of road, inscribed SURVEY MARK, with a steel washer inscribed BLM CADASTRAL SURVEY and mkd. 2011.</p> <p>from which</p> <p style="padding-left: 40px;">A right-of-way monument, bears N. 83¾° E., 180.0 lks. dist., measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the surface of the ground, plainly mkd. ROW on W. face.</p>

Subdivision of Section 1,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p style="text-align: center;">A right-of-way monument, bears S. 13¼° W., 678.1 lks. dist., measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the surface of the ground, plainly mkd. ROW on E. face.</p>
39.31	<p>The center W. 1/16 sec. cor. of sec. 1.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center S. 1/16 sec. cor. of sec. 1.</p> <p>N. 89° 06' W., beginning new measurement.</p> <p>Over rolling terrain.</p>
19.92	<p>The SW. 1/16 sec. cor. of sec. 1.</p>
38.69	<p>Center of railroad track, bears NNE. and SSW.</p>
39.83	<p>The S. 1/16 sec. cor. of secs. 1 and 2.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 3, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center S. 1/16 sec. cor. of sec. 3, monumented by person(s) unknown, with a solid iron axle, 32 ins. long, 1¼ ins. square, with rounded 1 in. diam. ends, firmly set flush with the surface of the ground, with granite stone, 9x8x4 ins., no mks. visible, and glass fragments buried alongside, located 2 lks. N. of railroad tie cor. post of fences extending E. and S. This position is recorded in Official Record of Survey Book No. 3, p. 57, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, with brass cap mkd.</p>

Dependent Resurvey, Subdivision of Section 3,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E C S 1/16 S 3 C 2011</p> <p>Deposit the iron axle inside, and bury the unmkd. stone and the glass fragments in a plastic bag and set a fiberglass sign post alongside, the iron post.</p> <p>From this point, a position of unknown origin or purpose, bears S. 79° 08' E., 3.4 lks. dist., monumented with an iron pipe, 1 in. diam., firmly set projecting 6 ins. above the surface of the ground. This position is not utilized during the course of this resurvey. Drive the iron pipe in place, flush with the surface of the ground.</p> <p>N. 0° 55' W., on the N. and S. center line of sec. 3.</p> <p>Over rolling terrain.</p>
19.91	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R8E C 1/4 S 3 2011</p>
39.87	<p>Point for the center N. 1/16 sec. cor. of sec. 3, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C N 1/16 S 3 C 2011</p>

Dependent Resurvey, Subdivision of Section 3,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
59.315	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2002-03 dependent resurvey of T. 26 N., R. 8 E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p> <p>N. 89° 21' W., on the E. and W. center line of sec. 3.</p> <p>Over rolling terrain.</p>
19.982	<p>Point for the center E. 1/16 sec. cor. of sec. 3, at proportionate distance, falls in E. ditch of gravel surfaced road extending N. and S.; there is no remaining evidence of the original cor. or the cor. recorded in the Thurston County Courthouse. Point not monumented.</p>
39.965	<p>The center 1/4 sec. cor. of sec. 3.</p>
60.135	<p>Point for the center W. 1/16 sec. cor. of sec. 3, at proportionate distance, falls in cultivated field on E. edge of field access road extending N. and S., there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E W 1/16 C ——— C S 3 2011</p> </div>
80.305	<p>The 1/4 sec. cor. of secs. 3 and 4.</p> <hr/> <div style="text-align: center;"> <p>Subdivision of Section 3, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> </div> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 3.</p> <p>N. 0° 42' W., on the N. and S. center line of the NW¼ of sec. 3.</p> <p>Over rolling terrain, along E. edge of field access road.</p>

Subdivision of Section 3,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
19.965	<p>Point for the NW. 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the NW¹/₄, falls in cultivated field on E. edge of field access road extending N. and S.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E NW 1/16 S 3 2011</p> <p>Cor. is located S. 81¾° E., 50 lks. dist., from intersection of fences extending N. and W.</p>
39.24	<p>The W. 1/16 sec. cor. for secs. 3, on the N. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2002-03 dependent resurvey of T. 26 N., R. 8 E.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 3.</p> <p>N. 89° 20' W., on the E. and W. center line of the NW¹/₄ of sec. 3.</p> <p>Over rolling terrain.</p>
20.09	<p>The NW. 1/16 sec. cor. of sec. 3.</p>
40.18	<p>The N. 1/16 sec. cor. of secs. 3 and 4.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 4, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the dependent resurvey executed by Richard A. Kohler in 1993)</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 4, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set a fiberglass sign post alongside the iron post.</p>

Dependent Resurvey, Subdivision of Section 4,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>N. 0° 27' W., on the N. and S. center line of sec. 4.</p> <p>Over rolling terrain.</p>
19.92	<p>Point for the center N. 1/16 sec. cor. of sec. 4, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E</p> <p>C</p> <p>N 1/16 S 4</p> <p>C</p> <p>2011</p> </div> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located N. 6¼° W., 6 lks. dist., from intersection of fences extending E. and S. with abandoned fence extending W.</p>
39.59	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>S. 89° 25' W., on the E. and W. center line of sec. 4.</p> <p>Over rolling terrain.</p>
20.065	<p>Point for the center E. 1/16 sec. cor. of sec. 4, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E</p> <p>E 1/16</p> <p>C ——— C</p> <p>S 4</p> <p>2011</p> </div> <p>Set a fiberglass sign post alongside the iron post.</p>

Dependent Resurvey, Subdivision of Section 4,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Cor. is located 3 lks. S. of fence extending E. and W.</p> <p>40.13 The center 1/4 sec. cor. of sec. 4.</p> <hr/> <p>S. 89° 37' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>20.075 The center W. 1/16 sec. cor. of sec. 4, monumented by person(s) unknown, with a vitrified clay tile, 26 ins. long, 4 ins. diam., firmly set 4 ins. below the surface of the ground, in fence extending E. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, inside the vitrified clay tile, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E W 1/16 C ——— C S 4 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <hr/> <p>S. 89° 39' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>20.065 The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 4.</p> <p>N. 0° 28' W., on the N. and S. center line of the NE¼ of sec. 4.</p>
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 4,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
19.945	<p>Over rolling terrain.</p> <p>Point for the NE. 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E NE 1/16 S 4 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 41¼° W., 2 lks. dist., from cor. post of fences extending N. and W.</p>
39.335	<p>The E. 1/16 sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 3 and 4.</p> <p>S. 89° 21' W., on the E. and W. center line of the NE¼ of sec. 4.</p> <p>Over rolling terrain.</p>
20.06	<p>The NE. 1/16 sec. cor. of sec. 4.</p>
40.12	<p>The center N. 1/16 sec. cor. of sec. 4.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 4.</p> <p>N. 0° 27' W., on the N. and S. center line of the NW¼ of sec. 4.</p> <p>Over rolling terrain.</p>
19.925	<p>Point for the NW. 1/16 sec. cor. of sec. 4, at intersection with the E. and W. center line of the NW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Subdivision of Section 4,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>T25N R8E NW 1/16 S 4 2011</p>
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 62½° W., 13 lks. dist., from cor. of fences extending N. and E., in remains of older abandoned fences and pile of field stones.</p>
39.775	<p>The W. 1/16 sec. cor. of secs. 4 and 33.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 4.</p> <p>S. 89° 39' W., on the E. and W. center line of the NW¼ of sec. 4.</p> <p>Over rolling terrain.</p>
20.07	<p>The NW. 1/16 sec. cor. of sec. 4.</p>
40.135	<p>The N. 1/16 sec. cor. of secs. 4 and 5.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 5, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 2008 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <p>N. 0° 26' W., on the N. and S. center line of sec. 5.</p> <p>Over rolling terrain, along E. side of gravel surfaced road right-of-way.</p>
20.00	<p>Point for the center S. 1/16 sec. cor. of sec. 5, at proportionate distance, falls in E. right-of-way of gravel surfaced road extending N. and S.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey, Subdivision of Section 5,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C S 1/16 S 5 C 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p>
40.00	<p>Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C 1/4 S 5 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located N. 41¾° W., 3 lks. dist., from intersection of fences extending N., E. and S.</p> <p>From this point, a position established in 1988 by Wayne W. Wheeler, Nebraska Registered Land Surveyor No. 211, bears N. 87° 39' W., 23.3 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set 12 ins. below the surface of E. ditch of gravel road extending N. and S., with aluminum cap mkd. GOVERNMENT CORNER TWP25 R8E CTR 5 LS211 and a cross. This monument is not located at the position shown on the Plat of Survey recorded in Plat Book No. 5, p. 45, in the Thurston County Courthouse, and is not accepted as a careful and faithful reestablishment of the original cor. position.</p>
60.005	<p>Point for the center N. 1/16 sec. cor. of sec. 5, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Subdivision of Section 5,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E C N 1/16 S 5 C 2011</p>
80.01	<p>Set a fiberglass sign post alongside the stainless steel post.</p> <p>Cor. is located 8 lks. W. of E. right-of-way fence of road extending N. and S.</p> <p>The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 26 N., R. 8 E.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>N. 89° 58' W., on the E. and W. center line of sec. 5.</p> <p>Over rolling terrain.</p>
19.955	<p>Point for the center E. 1/16 sec. cor. of sec. 5, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.</p>
39.91	<p>The center 1/4 sec. cor. of sec. 5.</p>
41.65	<p>The 1/4 sec. cor. of secs. 1 and 5, on the W. bdy. of the Tp.</p> <hr/>
	<p style="text-align: center;">Subdivision of Section 5, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/>
	<p>From the center S. 1/16 sec. cor. of sec. 5.</p> <p>S. 89° 55' W., on the E. and W. center line of the SW¼ of sec. 5.</p> <p>Over rolling terrain.</p>
1.87	<p>The S. 1/16 sec. cor. of secs. 1 and 5, on the W. bdy. of the Tp.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 5.</p>

Subdivision of Section 5,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p>N. 89° 57' W., on the E. and W. centerline of the NW¼ of sec. 5.</p> <p>Over rolling terrain.</p>
1.61	<p>The N. 1/16 sec. cor. of secs. 1 and 5, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 12, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 12 and 13.</p> <p>N. 0° 18' W., on the N. and S. center line of sec. 12.</p> <p>Over rolling terrain.</p>
19.975	<p>Point for the center S. 1/16 sec. cor. of sec. 12, at proportionate distance, falls in livestock feedlot; there is no remaining evidence of the original cor. Point not monumented.</p>
39.95	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E. and W. center line, falls in cultivated field; there is no remaining evidence of the original cor. or the cor. recorded in the Thurston County Courthouse.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C 1/4 S 12 2011</p>
59.90	<p>Point for the center N. 1/16 sec. cor. of sec. 12, at proportionate distance, falls on edge of cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Subdivision of Section 12,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E C N 1/16 S 12 C 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a solid iron grounding rod for an electric fence, ½ in. diam., firmly set 8 ins. below the surface of the ground, bears N. 61° 39' E., 33.4 lks. dist. This position is not utilized during the course of this resurvey.</p> <p>Cor. is located 16 lks. S. of irregular fence extending E. and W.</p> <p>79.85 The 1/4 sec. cor. of secs. 1 and 12.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 88° 55' W., on the E. and W. center line of sec. 12.</p> <p>Over rolling terrain.</p>
19.92	<p>Point for the center E. 1/16 sec. cor. of sec. 12, at proportionate distance, falls on W. edge of access road in livestock feedlot; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
39.84	<p style="text-align: center;">T25N R8E E 1/16 C ——— C S 12 2011</p> <p>The center 1/4 sec. cor. of sec. 12.</p>
58.24	<p>U.S. Highway No. 77, bears N. and S.</p>
59.86	<p>The center W. 1/16 sec. cor. of sec. 12, monumented in 1967 by R. H. Starman, Nebraska State Dept. of Roads, with a solid iron shaft, 24 ins. long,</p>

Dependent Resurvey, Subdivision of Section 12,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>1 in. square, firmly set 6 ins. below the surface of the ground. This position is recorded in Surveyor's Record Book No. 2, p. 249, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E W 1/16 C ——— C S 12 2011</p> <p>Deposit the iron shaft inside and set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 1 lk. dist. from the NW. cor. of tapered concrete right-of-way monument, firmly set projecting 20 ins. above the ground, 2 lks. E. of W. right-of-way fence of U.S. Highway No. 77, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 47' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>19.85 The 1/4 sec. cor. of secs. 11 and 12.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">Subdivision of Section 12, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the center E. 1/16 sec. cor. of sec. 12.</p> <p>N. 0° 10' W., on the N. and S. center line of the NE¼ of sec. 12.</p> <p>Over rolling terrain.</p> <p>19.95 Point for the NE. 1/16 sec. cor. of sec. 12, at intersection with the E. and W. center line of the NE¼, falls in cultivated field.</p>
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 12,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E NE 1/16 S 12 2011</p> <p>Cor. is located S. 70½° E., 62 lks. dist., from cor. of fences extending N. and W.</p>
39.90	<p>The E. 1/16 sec. cor. of secs. 1 and 12.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 88° 55' W., on the E. and W. center line of the NE¼ of sec. 12.</p> <p>Over rolling terrain.</p>
19.96	<p>The NE. 1/16 sec. cor. of sec. 12.</p>
39.92	<p>The center N. 1/16 sec. cor. of sec. 12.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 12.</p> <p>N. 0° 07' W., on the N. and S. center line of the NW¼ of sec. 12.</p> <p>Over rolling terrain.</p>
19.965	<p>Point for the NW. 1/16 sec. cor. of sec. 12, at intersection with the E. and W. center line of the NW¼, falls in W. ditch of U.S. Highway No. 77.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E NW 1/16 S 12 2011</p>

Subdivision of Section 12,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A right-of-way monument, bears N. 66° E., 338.0 lks. dist., measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the surface of the ground, plainly mkd. ROW on W. face.</p> <p style="padding-left: 40px;">A right-of-way monument, bears N. 87° E., 238.7 lks. dist., measured to center of a shattered tapered concrete post, firmly set projecting 10 ins. above the surface of the ground.</p> <p style="padding-left: 40px;">A right-of-way monument, bears N. 4¼° W., 581.4 lks. dist., measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the surface of the ground, plainly mkd. ROW on E. face.</p>
39.97	<p>The W. 1/16 sec. cor. of secs. 1 and 12.</p> <hr style="width: 60%; margin-left: 40px;"/> <p>From the center N. 1/16 sec. cor. of sec. 12.</p> <p>N. 88° 52' W., on the E. and W. center line of the NW¼ of sec. 12.</p> <p>Over rolling terrain.</p>
18.85	<p>U.S. Highway No. 77, bears N. and S.</p>
19.955	<p>The NW. 1/16 sec. cor. of sec. 12.</p>
39.815	<p>The N. 1/16 sec. cor. of secs. 11 and 12.</p> <hr style="width: 60%; margin-left: 40px;"/>

Dependent Resurvey, Subdivision of Section 13,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set fiberglass sign posts alongside the 1993 reference monuments.</p> <p>N. 0° 05' E., on the N. and S. center line of sec. 13.</p> <p>Over rolling terrain.</p>
19.91	<p>Point for the center S. 1/16 sec. cor. of sec. 13, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E C S 1/16 S 13 C 2011</p> </div> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 5 lks. E. of fences extending N. and S.</p>
39.82	<p>The center 1/4 sec. cor. of sec. 13, monumented by person(s) unknown with a fragmented vitrified clay tile, firmly set 42 ins. below the ground at base of cor. post of abandoned fences extending N., E. and S. This position is recorded in Surveyor's Record Book No. 1, p. 236, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a steel fence post, with brass cap mkd.</p>

Dependent Resurvey, Subdivision of Section 13,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E C 1/4 S 13 2011</p> <p>Bury the tile fragments and a plastic encased magnetic marker in a plastic bag and set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located N. $10\frac{1}{4}^{\circ}$ E., 12 lks. dist., from intersection of abandoned fences extending N., S. and W.</p> <hr style="width: 25%; margin: 10px auto;"/> <p>N. $0^{\circ} 23'$ E., beginning new measurement.</p> <p>Over rolling terrain.</p>
20.05	<p>Point for the center N. 1/16 sec. cor. of sec. 13, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.</p>
40.10	<p>The 1/4 sec. cor. of secs. 12 and 13.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. $89^{\circ} 14'$ W., on the E. and W. center line of sec. 13.</p> <p>Over rolling terrain.</p>
19.955	<p>Point for the center E. 1/16 sec. cor. of sec. 13, at proportionate distance, falls in grass field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E E 1/16 C ——— C S 13 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p>

Dependent Resurvey, Subdivision of Section 13,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>Cor. is located N. 64° W., 17 lks. dist., from intersection of fences extending N., E. and W.</p> <p>39.91 The center 1/4 sec. cor. of sec. 13.</p> <hr/> <p>N. 88° 56' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>18.415 U.S. Highway No. 77, bears N. and S.</p> <p>19.775 Point for the center W. 1/16 sec. cor. of sec. 13, at proportionate distance, falls on edge of cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E W 1/16 C ——— C S 13 2011</p> <p>from which</p> <p style="padding-left: 40px;">A right-of-way monument, bears N. 82½° E., 53.6 lks. dist. measured to center of top face, monumented with a tapered concrete post, 4x8 ins. at the top, firmly set projecting 20 ins. above the ground, plainly mkd. ROW on E. face.</p> <p>From this point, a position established in 1966 by R. H. Starman, Nebraska State Dept. of Roads, bears S. 85° 49' E., 107.8 lks. dist., monumented with a steel reinforcement rod, 1 in. diam., firmly set 8 ins. below the W. asphalt apron of U.S. Highway No. 77, extending N. and S., as recorded in Surveyor's Record Book No. 2, p. 249, in the Thurston County Courthouse. This position is attributed to a position monumented in 1964 by Ziba N. Dewey, Nebraska Registered Land Surveyor No. 137, as recorded in Surveyor's Record Book No. 2, p. 211, in the Thurston County Courthouse. After conversations with the Nebraska State Dept. of Roads office in Lincoln, Nebraska, finding no corroborating records of where this position originated and viewing conflicting strip map evidence circa 1946, it was concluded that this position is not accepted as the best available evidence of the original cor. position.</p>
----------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 13,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>From this same point, U.S. Coast and Geodetic Bench Mark E237, bears N. 79° 35' E., 54.0 lks. dist., monumented with a concrete post, 5 ins. square, firmly set, projecting 4 ins. above the ground, with brass tablet inscribed U.S. COAST AND GEODETIC SURVEY BENCH MARK and mkd. E237, with a steel fence post alongside.</p>
<p>39.55</p>	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">Subdivision of Section 13, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the center E. 1/16 sec. cor. of sec. 13.</p> <p>N. 0° 11' E., on the N. and S. center line of the NE¼ of sec. 13.</p> <p>Over rolling terrain.</p>
<p>40.00</p>	<p>The E. 1/16 sec. cor. of secs. 12 and 13.</p> <hr/> <p>From the W. 1/16 sec. cor. of sec. 13 and 24, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E.</p> <p>N. 0° 12' E., on the N. and S. center line of the SW¼ of sec. 13.</p> <p>Over rolling terrain.</p>
<p>19.925</p>	<p>Point for the SW. 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E SW 1/16 S 13 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p>

Subdivision of Section 13,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p>Cor. is located N. 82° E., 2 lks. dist., from cor. of abandoned fences extending N. and W.</p>
39.85	<p>The center W. 1/16 sec. cor. of sec. 13.</p> <hr/> <p>From the center S. 1/16 sec. cor. of sec. 13.</p> <p>N. 88° 59' W., on the E. and W. center line of the SW¼ of sec. 13.</p> <p>Over rolling terrain.</p>
17.30	<p>U.S. Highway No. 77, bears SSE. and NNW.</p>
19.82	<p>The SW. 1/16 sec. cor. of sec. 13.</p>
39.64	<p>The S. 1/16 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 14, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 07' W., on the N. and S. center line of sec. 14.</p> <p>Over rolling terrain.</p>
19.80	<p>Point for the center S. 1/16 sec. cor. of sec. 14, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Subdivision of Section 14,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	T25N R8E C S 1/16 S 14 C 2012
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 5 lks. W. of fence extending N. and S.</p>
29.70	<p>Point for the center N-S 1/64 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
	T25N R8E C N-S 1/64 S 14 C 2012
	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 2¾° W., 93 lks. dist., from intersection of fences extending N., S. and W.</p> <p>From this point, a position established in 1929 by H. B. Lawson, Deputy State Surveyor, bears S. 53° 41' W., 4.6 lks. dist., monumented with an iron pipe, 1¼ ins. diam., firmly set 48 ins. below the surface of the ground, as filed in the Thurston County Courthouse. This position was established based on erroneous control and is not accepted as a careful and faithful establishment of the cor. position.</p>
35.80	<p>Nebraska State Highway No. 94, bears NE. and SW.</p>
39.60	<p>The center 1/4 sec. cor. of sec. 14, monumented with an iron post, 2½ ins. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set a fiberglass sign post alongside the iron post.</p> <p>From this point, the 1/4 sec. cor. of secs. 13 and 14, bears N. 89° 16' E., 40.05 chs. dist. This tie is provided for informative purposes only; the intervening cor. was not searched for.</p> <hr style="width: 50%; margin-left: auto; margin-right: auto;"/>

Dependent Resurvey, Subdivision of Section 14,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>From the center 1/4 sec. cor. of sec. 14.</p> <p>S. 89° 55' W., on the E. and W. center line of sec. 14.</p> <p>Over rolling terrain.</p> <p>10.16 Point for center E-W 1/64 sec. cor. of sec. 14, at proportionate dist. by method of irregular boundary adjustment based on 1993 dependent resurvey record; there is no remaining evidence of the monument recovered in 1993.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E E-W 1/64 C ——— C S 14 2012</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 1.5 lks. S. of recently set railroad tie cor. post in abandoned fences extending N. and W.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 45' W., beginning new measurement.</p> <p>Over rolling terrain.</p> <p>10.02 The center W. 1/16 sec. cor. of sec. 14, monumented with an aluminum rod, ⅜ in. diam., as described in the field notes of the 1993 dependent resurvey of a portion of T. 25 N., R. 8 E. Set a fiberglass sign post alongside the iron post.</p> <hr style="width: 60%; margin: auto;"/> <p style="text-align: center;">Subdivision of Section 14, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr style="width: 60%; margin: auto;"/> <p>From the W. 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 33' W., on the N. and S. center line of the SW¼ of sec. 14.</p> <p>Over rolling terrain.</p>
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 14,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
12.90	Nebraska State Highway No. 94, bears NE. and SW.
19.895	<p>Point for the SW. 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the SW$\frac{1}{4}$.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E SW 1/16 S 14 2012</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 8 lks. E. of fence extending N. and S.</p>
29.775	<p>Point for the center N-SW 1/64 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C-N-SW 1/64 S 14 2012</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 7 lks. E. of fence extending N. and S.</p>
39.655	<p>The center W. 1/16 sec. cor. of sec. 14.</p> <hr style="width: 50%; margin-left: 0;"/> <p>From the center S. 1/16 sec. cor. of sec. 14.</p> <p>S. 89° 56' W., on the E. and W. center line of the SW$\frac{1}{4}$ of sec. 14.</p> <p>Over rolling terrain.</p>
10.015	Point for the center E-SW 1/64 sec. cor. of sec. 14, falls in cultivated field.

Subdivision of Section 14,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C-E-SW 1/64 S 14 2012</p>
13.90	Nebraska State Highway No. 94, bears NE. and SW.
20.03	The SW. 1/16 sec. cor. of sec. 14.
39.68	The S. 1/16 sec. cor. of secs. 14 and 15.
	<hr/> <p>From the center E-SW 1/64 sec. cor. of sec. 14.</p> <p>N. 0° 32' W., on the N. and S. center line of the NE¼SW¼ of sec. 14.</p> <p>Over rolling terrain.</p>
4.50	Nebraska State Highway No. 94, bears NE. and SW.
9.89	Point for the NE-SW 1/64 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NE¼SW¼.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E NE-SW 1/64 S 14 2012</p>
19.795	<p>Set a fiberglass sign post alongside the iron post.</p> <p>The center E-W 1/64 sec. cor. of sec. 14.</p> <hr/> <p>From the center N-S 1/64 sec. cor. of sec. 14.</p> <p>S. 89° 53' W., on the E. and W. center line of the NE¼SW¼ of sec. 14.</p> <p>Over rolling terrain.</p>

Subdivision of Section 14,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
5.40	Nebraska State Highway No. 94, bears NE. and SW.
10.09	The NE-SW 1/64 sec. cor. of sec. 14.
20.11	The center N-SW 1/64 sec. cor. of sec. 14.
	<hr/> Dependent Resurvey, Subdivision of Section 15, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska <hr/> (Restoring the survey executed by Theodore H. Barrett in 1867) <hr/>
	From the 1/4 sec. cor. of secs. 15 and 22.
	N. 0° 08' E., on the N. and S. center line of sec. 15.
	Over rolling terrain.
20.01	Point for the center S. 1/16 sec. cor. of sec. 15, at proportionate distance; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.
	T25N R8E C S 1/16 S 15 C 2011
	Set a fiberglass sign post alongside the iron post.
	Cor. is located N. 9° E., 14 lks. dist., from projected intersection of abandoned fences extending N., E. and S.
40.02	The center 1/4 sec. cor. of sec. 15, at lower decayed portion of cor. post of abandoned fences extending N., S. and W. This position is accepted as the best available evidence of the original cor. position.
	At the corner point

Dependent Resurvey, Subdivision of Section 15,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C 1/4 S 15 2011</p> <p>Buried the decayed post and set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 74¾° E., 6 lks. dist., from intersection of fences extending N., S. and W.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89° 54' W., on the E. and W. center line of sec. 15.</p> <p>Over rolling terrain.</p>
20.037	<p>Point for the center E. 1/16 sec. cor. of sec. 15, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. Point not monumented.</p>
40.075	<p>The center 1/4 sec. cor. of sec. 15.</p> <hr/> <p style="text-align: center;">Subdivision of Section 15, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the S. 1/16 sec. cor. of secs. 14 and 15.</p> <p>N. 89° 56' W., on the E. and W. center line of the SE¼ of sec. 15.</p> <p>Over rolling terrain.</p>
40.095	<p>The center S. 1/16 sec. cor. of sec. 15.</p> <hr/>

Dependent Resurvey, Subdivision of Section 21,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p>(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>S. 89° 50' W., on the E. and W. center line of sec. 21.</p> <p>Over rolling terrain.</p>
19.78	<p>Point for the center E. 1/16 sec. cor. of sec. 21, at proportionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;"> T25N R8E E 1/16 C ——— C S 21 2011 </p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 74¼° W., 10 lks. dist., from intersection of newly reconstructed fences extending N. and E. with abandoned fence extending W.</p>
39.56	<p>The center 1/4 sec. cor. of sec. 21, at lower decayed portion of cor. post of fences extending E., S. and W., on W. side of iron I-beam currently utilized as cor. post. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;"> T25N R8E C 1/4 S 21 2011 </p> <p>Set a fiberglass sign post alongside the iron post.</p> <hr/>

Subdivision of Section 21,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	<p>From the center E. 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 24' E., on the N. and S. center line of the NE¼ of sec. 21.</p> <p>Over rolling terrain.</p>
39.83	<p>The E. 1/16 sec. cor. of secs. 16 and 21.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 26, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0° 07' W., on the N. and S. center line of sec. 26.</p> <p>Over rolling terrain.</p>
10.385	<p>SW. cor. of parcel bears WEST, 57.7 lks. dist., established in 1990 by Richard C. Johnson, Nebraska Registered Land Surveyor No. 429, monumented with an iron pipe, 1 in. diam., firmly set projecting 2 ins. above the ground, as recorded in Plat Book No. 6, p. 14, in the Thurston County Courthouse.</p>
16.20	<p>NW. cor. of parcel bears WEST, 77.4 lks. dist., established in 1990 by Richard C. Johnson, Nebraska Registered Land Surveyor No. 429, monumented with an iron pipe, 1 in. diam., firmly set projecting 2 ins. above the ground, as recorded in Plat Book No. 6, p. 14., in the Thurston County Courthouse.</p>
20.04	<p>Point for the center S. 1/16 sec. cor. of sec. 26, at proportionate distance, falls in cultivated; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Dependent Resurvey, Subdivision of Section 26,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E C S 1/16 S 26 C 2011</p> <p>From this point, a position established in 1990 by Clyde R. Flowers, Jr., Nebraska Registered Land Surveyor No. 357, bears N. 81° 25' W., 92.0 lks. dist., monumented with a steel reinforcement rod, 5/8 in. diam., firmly set 16 ins. below the surface of cultivated field, with aluminum cap mkd. RLS357 S1/16 COR. 26 DO NOT DISTURB SURVEY MARK, as recorded on a record obtained from the Nebraska State Surveyor's Office. This position was established by erroneous methods utilizing erroneous controlling cor. position to the S., was not recovered at platted position, and is not accepted as a careful and faithful reestablishment of the original cor. position.</p>
40.08	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E. and W. center line; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
	<p style="text-align: center;">T25N R8E C 1/4 S 26 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>From this point, a calculated position established in 2005 by Terry L. Schulz, Nebraska Registered Land Surveyor No. 550, bears N. 42° 01' W., 7.8 lks. dist., point not monumented. This position is shown on a plat obtained from Mr. Schulz, was established by erroneous methods utilizing erroneous control to the S., ignoring controlling cor. to the W., and is not accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>Cor. is located N. 12° E., 32 lks. dist., from decayed railroad tie cor. post of abandoned fences extending N., E. and W.</p>
58.75	<p>Projection of abandoned fence from the W.</p>
60.09	<p>Point for the center N. 1/16 sec. cor. of sec. 26, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.</p>

Dependent Resurvey, Subdivision of Section 26,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
80.10	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented by person(s) unknown, with an iron pipe, 1 in. diam., firmly set 32 ins. below gravel surfaced road extending E. and W., with a solid iron shaft, 23 ins. long, 1 3/4 ins. diam., and glass and wood fragments alongside, and with an iron pipe, 30 ins. long, 1 1/4 ins. diam., with solid iron rod, 1/2 in. square, driven in the center, set over the top, in projection of fence from the S. This position is recorded in Surveyor's Record Book No. 1, p. 247, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. below the surface of the road, atop the 1 in. iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E S 23 1/4 ——— S 26 2011</p> </div> <p>Bury the glass and wood fragments in a plastic bag alongside the iron post. Remove the remaining iron monuments from the vicinity.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears NORTH, 50.3 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S23 33.2 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 2 1/2° W., 50.0 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S26 33.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, monumented in 2005 by Terry L. Schulz, Nebraska Registered Land Surveyor No. 550, with a steel reinforcement rod, 24 ins. long, 5/8 in. diam., firmly set 6 ins. below the E. edge of gravel surfaced road extending N. and S., with orange plastic cap</p>

Dependent Resurvey, Subdivision of Section 26,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>mkd. SCHULZ RLS 550. This position is shown on a plat obtained from Mr. Schulz, and is accepted as a careful and faithful reestablishment of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E 1/4 S 26 S 25 2011</p> </div> <p>Deposit the steel reinforcement rod inside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 89° E., 39.6 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S25 26.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 86¾° W., 55.3 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S26 36.5 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>Cor. is located in projection of fence from the W. and field division line from the E.</p> <p>N. 89° 50' W., on the E. and W. center line of sec. 26.</p> <p>Over rolling terrain.</p> <p>0.50 NE. cor. of parcel established in 2005 by Terry L. Schulz, Nebraska Registered Land Surveyor No. 550, monumented with a steel reinforcement rod, 5/8 in. diam., with orange plastic cap mkd. SCHULZ RLS 550, firmly set flush with the surface of the ground, as shown on a plat obtained from Mr. Schulz.</p>
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 26,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
6.575	NW. cor. of parcel bears NORTH, 1.2 lks. dist., established in 2005 by Terry L. Schulz, Nebraska Registered Land Surveyor No. 550, monumented with a steel reinforcement rod, 5/8 in. diam., with orange plastic cap mkd. SCHULZ RLS 550, firmly set flush with the surface of the ground, as shown on a plat obtained from Mr. Schulz.
20.07	Point for the center E. 1/16 sec. cor. of sec. 26, at proportionate distance; there is no remaining evidence of the original cor. Point not monumented.
40.14	The center 1/4 sec. cor. of sec. 26.
55.80	Gravel surfaced road, bears NNE. and SSW.
57.76	Center of railroad track, bears NNE. and SSW.
60.255	Point for the center W. 1/16 sec. cor. of sec. 26, at proportionate distance, falls on edge of cultivated field 37 lks. N. of abandoned fence extending E. and W.; there is no remaining evidence of the original cor. Point not monumented.
80.37	The 1/4 sec. cor. of secs. 26 and 27.
<hr/> Subdivision of Section 26, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska <hr/>	
	From the center S. 1/16 sec. cor. of sec. 26.
	N. 89° 51' W., on the E. and W. center line of the SW ¹ / ₄ of sec. 26.
	Over rolling terrain.
21.00	Gravel surfaced road, bears NNE. and SSW.
23.11	Center of railroad track, bears NNE. and SSW.
40.31	The S. 1/16 sec. cor. of secs. 26 and 27.

Dependent Resurvey, Subdivision of Section 33,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr style="width: 20%; margin: auto;"/> <p>From the center 1/4 sec. cor. of sec. 33, at cor. post of intersection of abandoned fences extending NE., S. and WNW. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C 1/4 S 33 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located on S. bank of small creek, drains ENE.</p> <p>From this point, the 1/4 sec. cor. of sec. 33 and 34, hereinafter described, bears S. 89° 56' E., 39.83 chs. dist. This tie is provided for informative purposes only; the intervening cor. was not searched for.</p> <p>From this same point, the standard 1/4 sec. cor. of sec. 33, on the S. bdy. of the Tp., bears S. 0° 14' E., 40.005 chs. dist., monumented with an iron pipe, 30 ins. long, 3 ins. diam., firmly set 12 ins. below N. lane of gravel surfaced road extending E. and W., with glass and paving brick fragments alongside, in projection of fence from the N. This position is recorded in Surveyor's Record Book No. 1, p. 204, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of the road, atop the reset iron pipe, with brass cap mkd.</p>
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 33,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
20.045	<p>Point for the center N. 1/16 sec. cor. of sec. 33, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C N 1/16 S 33 C 2011</p> <p>Cor. is located S. 10½° E., 66 lks. dist., from cor. of fences extending N. and E.</p>
40.09	<p>The 1/4 sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the center 1/4 sec. cor. of sec. 33.</p> <p>N. 89° 56' W., on the E. and W. center line of sec. 33.</p> <p>Over rolling terrain.</p>
1.20	<p>Small creek, drains NE.</p>
19.94	<p>Point for the center W. 1/16 sec. cor. of sec. 33, at proportionate distance, falls in division between cultivated fields; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E W 1/16 C ——— C S 33 2011</p>
39.88	<p>The 1/4 sec. cor. of secs. 32 and 33.</p> <hr/>

Subdivision of Section 33,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p> <p>20.04</p> <p>40.08</p> <p>19.895</p> <p>39.79</p>	<p>From the center W. 1/16 sec. cor. of sec. 33.</p> <p>N. 0° 10' W., on the N. and S. center line of the NW¼ of sec. 33.</p> <p>Over rolling terrain.</p> <p>Point for the NW. 1/16 sec. cor. of sec. 33, at intersection with the E. and W. center line of the NW¼, falls on edge of cultivated field.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E NW 1/16 S 33 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 21 lks. N. of projection of field division line from the W.</p> <p>The W. 1/16 sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 33.</p> <p>N. 89° 56' W., on the E. and W. center line of the NW¼ of sec. 33.</p> <p>Over rolling terrain.</p> <p>The NW. 1/16 sec. cor. of sec. 33.</p> <p>The N. 1/16 sec. cor. of secs. 32 and 33.</p> <hr/> <p style="text-align: center;">Dependent Resurvey, Subdivision of Section 34, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the standard 1/4 sec. cor. of sec. 34, on the S. bdy. of the Tp.</p>
---------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 34,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>N. 0° 09' W., on the N. and S. center line of sec. 34.</p> <p>Over rolling terrain.</p> <p>20.03 Point for the center S. 1/16 sec. cor. of sec. 34, at proportionate distance, falls 15 lks. E. of abandoned fence extending N. and S.; there is no remaining evidence of the original cor. Point not monumented.</p> <p>40.06 Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E. and W. center line; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C 1/4 S 34 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located S. 45¾° E., 17 lks. dist., from recently constructed cor. of fences extending N. and W., with abandoned fences extending E. and S.</p> <p>60.225 Point for the center N. 1/16 sec. cor. of sec. 34, at proportionate distance, falls on edge of cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C N 1/16 S 34 C 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 9 lks. W. of projection of abandoned fence from the N.</p> <p>80.39 The 1/4 sec. cor. of secs. 27 and 34, monumented by person(s) unknown, with an iron pipe, 1½ ins. diam., firmly set 53 ins. below dirt surfaced road extending E. and W., upper 10 in. section of same iron pipe set alongside, with vitrified clay tile, glass and wood fragments around base. This position</p>
----------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 34,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>is recorded in Surveyor's Record Book No. 1, p. 248, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E S 27 1/4—— S 34 2011</p> </div> <p>Bury the clay tile, glass and wood fragments in a plastic bag alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 6½° E., 41.0 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S34 27.1 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 0½° W., 45.2 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S27 29.8 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>From this point, the cor. of secs. 26, 27, 34 and 35, bears S. 89° 31' E., 40.25 chs. dist. This tie is provided for informative purposes only; the intervening cor. was not searched for.</p> <p>From this same point, the cor. of secs. 27, 28, 33 and 34, bears S. 89° 47' W., 40.39 chs. dist. This tie is provided for informative purposes only; the intervening cor. was not searched for.</p> <hr style="width: 60%; margin-left: 0;"/> <p>From the 1/4 sec. cor. of secs. 34 and 35.</p>
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 34,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>N. 89° 53' W., on the E. and W. center line of sec. 34.</p> <p>Over rolling terrain.</p> <p>20.055 Point for the center E. 1/16 sec. cor. of sec. 34, at proportionate distance, falls S. 83½° E., 19 lks. dist., from intersection of fences extending E., S. and W.; there is no remaining evidence of the original cor. Point not monumented.</p> <p>40.11 The center 1/4 sec. cor. of sec. 34.</p> <p>60.195 Point for the center W. 1/16 sec. cor. of sec. 34, at proportionate distance, falls in cultivated field, N. 26½° W., 22 lks. dist., from recently constructed cor. of fences extending E. and S., there is no remaining evidence of the original cor. Point not monumented.</p> <p>80.28 The 1/4 sec. cor. of secs. 33 and 34, monumented by person(s) unknown, with an iron pipe, 25 ins. long, 1¾ ins. diam., firmly set flush with dirt surfaced road extending N. and S., with paving brick fragments alongside, and four granite stones, largest 15x10x8 ins., no mks. visible, buried alongside. This position is recorded in Official Record of Survey Book No. 3, p. 101, and Surveyor's Record Book No. 1, p. 252, in the Thurston County Courthouse, and is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the road, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E 1/4 S 33 S 34 2011</p> <p>Deposit the iron pipe inside, and bury the brick fragments in a plastic bag and largest unmkd. stone alongside, the iron post. Remove the remaining unmkd. stones from the vicinity.</p>
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 34,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 41¼° E., 58.6 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S34 38.7 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears WEST., 50.0 lks. dist., with brass cap mkd. RM T25N R8E 1/4 S33 33.0 FT. TO COR. 2011 and an arrow pointing to the cor., with a fiberglass sign post set alongside. This reference monument is set alongside the shattered remains of a triangular shaped concrete right-of-way monument, with solid iron rod, ½ in. diam., in the center.</p> <p>From this point, a right-of-way monument bears S. 89° 19' E., 50.2 lks. dist., monumented with a triangular shaped concrete post, firmly set 20 ins. below the surface of field access driveway, upper portion shattered, with solid iron rod, ½ in. diam., in the center.</p> <p>From this same point, the cor. of secs. 27, 28, 33 and 34, bears N. 0° 28' W., 40.095 chs. dist. This tie is provided for informative purposes only; the intervening cor. was not searched for.</p> <hr/> <p style="text-align: center;">Subdivision of Section 34, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 34 and 35.</p> <p>N. 89° 42' W., on the E. and W. center line of the NE¼ of sec. 34.</p> <p>Over rolling terrain.</p> <p>40.18 The center N. 1/16 sec. cor. of sec. 34.</p> <hr/>
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 36,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p style="text-align: center;">(Restoring the survey executed by Theodore H. Barrett in 1867)</p> <hr/> <p>From the standard 1/4 sec. cor. of sec. 36, identical with the 1/4 sec. cor. of sec. 1 only, T. 24 N., R. 8 E., on the S. bdy. of the Tp.</p> <p>N. 0° 47' E., on the N. and S. center line of sec. 36.</p> <p>Over rolling terrain, along abandoned fence.</p> <p>20.045 The center S. 1/16 sec. cor. of sec. 36, at decayed lower portion of cor. post of abandoned fences extending N., E., S. and W. This position is accepted as the best available evidence of the original cor. position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T25N R8E C S 1/16 S 36 C 2011</p> </div> <p>Set a fiberglass sign post alongside the iron post.</p> <hr/> <p>N. 0° 12' E., beginning new measurement.</p> <p>Over rolling terrain, along abandoned fence.</p> <p>20.02 Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E. and W. center line, falls in abandoned fence extending N. and S.; there is no remaining evidence of the original cor. or the monument recorded in the Thurston County Courthouse.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>
----------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Dependent Resurvey, Subdivision of Section 36,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
	<p style="text-align: center;">T25N R8E C 1/4 S 36 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Gradually leave abandoned fence from this point.</p>
40.095	<p>Point for the center N. 1/16 sec. cor. of sec. 36, at proportionate distance, falls on edge of cultivated field; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., flush with the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E C N 1/16 S 36 C 2011</p>
60.17	<p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located N. 13° W., 14 lks. dist., from projected intersection of abandoned fences extending N., E. and S.</p> <p>The 1/4 sec. cor. of secs. 25 and 36.</p> <hr style="width: 60%; margin-left: 0;"/>
	<p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 89° 47' W., on the E. and W. center line of sec. 36.</p> <p>Over rolling terrain.</p>
19.83	<p>Point for the center E. 1/16 sec. cor. of sec. 36, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. Point not monumented.</p>
39.66	<p>The center 1/4 sec. cor. of sec. 36.</p>

Dependent Resurvey, Subdivision of Section 36,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

Chains	
59.455	<p>Point for the center W. 1/16 sec. cor. of sec. 36, at proportionate distance, falls in cultivated field; there is no remaining evidence of the original cor. or the monument recorded in the Thurston County Courthouse.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. below the surface of the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p> <p style="text-align: center;">T25N R8E W 1/16 C ——— C S 36 2011</p>
79.25	<p>The 1/4 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">Subdivision of Section 36, T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp., monumented with a stainless steel post, 2½ ins. diam., as described in the field notes of the 2001-03 dependent resurvey of T. 25 N., R. 9 E.</p> <p>N. 89° 44' W., on the E. and W. center line of the NE¼ of sec. 36.</p> <p>Over rolling terrain.</p>
39.585	<p>The center N. 1/16 sec. cor. of sec. 36.</p> <hr/> <p>From the center W. 1/16 sec. cor. of sec. 36.</p> <p>N. 0° 21' E., on the N. and S. center line of NW¼ of sec. 36</p> <p>Over rolling terrain.</p>
20.065	<p>Point for the NW. 1/16 sec. cor. of sec. 36, at intersection with the E. and W. center line of the NW¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a plastic encased magnetic marker, with brass cap mkd.</p>

Subdivision of Section 36,
T. 25 N., R. 8 E., Sixth Principal Meridian, Nebraska

<p>Chains</p>	<p style="text-align: center;">T25N R8E NW 1/16 S 36 2011</p> <p>Set a fiberglass sign post alongside the iron post.</p> <p>Cor. is located 26 lks. N. of fence extending E. and W., and 83 lks. N. of gravel surfaced access road extending same.</p> <p>40.12 The W. 1/16 sec. cor. of secs. 25 and 36.</p> <hr/> <p>From the center N. 1/16 sec. cor. of sec. 36.</p> <p>N. 89° 49' W., on the E. and W. center line of the NW¼ of sec. 36.</p> <p>Over rolling terrain.</p> <p>19.745 The NW. 1/16 sec. cor. of sec. 36.</p> <p>39.56 The N. 1/16 sec. cor. of secs. 35 and 36.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area embraced by this resurvey is located in the Omaha Indian Reservation, in the central portion of Thurston County, Nebraska. The terrain is primarily rolling farmland with scattered patches of timber. The elevation ranges from about 1200 feet to about 1450 feet above sea level. The soil is primarily loam with large clay content and timber consists of various species of hardwoods. Drainage consists of North Omaha Creek, which courses southeasterly, and Omaha Creek, which courses northerly, aided by numerous major and minor draws and drainages. There was no indication of mineral activity at the time of the resurvey.</p> <p>Excellent access is provided by U.S. Highway No. 77, which traverses along the east boundary of the township, and Nebraska State Highway No. 94, which traverses east and west through the township, aided by numerous local roads throughout the area. There are numerous residences throughout, with the town of Walthill, Nebraska, located within sections 11 and 14.</p>
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD ASSISTANTS

NAMES	CAPACITY
Brent M. Skidmore	Surveying Technician

CERTIFICATE OF SURVEY

I, Ryan R. Lorenzen, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day of May, 2011, I have dependently resurveyed portions of the Sixth Standard Parallel North, through Range 8 East, the west and north boundaries, the subdivisional lines, and the subdivision of certain sections, and surveyed the subdivision of certain sections, Township 25 North, Range 8 East, of the Sixth Principal Meridian, in the State of Nebraska, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 26, 2013

/s/ Ryan R. Lorenzen

 Date

 Ryan R. Lorenzen
 Cadastral Surveyor

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Cheyenne, Wyoming

The foregoing field notes of the dependent resurvey of portions of the Sixth Standard Parallel North, through Range 8 East, the west and north boundaries, the subdivisional lines, and the subdivision of certain sections, and the survey of the subdivision of certain sections, Township 25 North, Range 8 East, Sixth Principal Meridian, Nebraska, executed by Ryan R. Lorenzen, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

March 26, 2013

/s/ John P. Lee

 Date

 John P. Lee
 Chief Cadastral Surveyor for Nebraska

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 25 N., R. 8 E., 6th Prin. Mer., Neb., is a true copy of the original field notes.

March 26, 2013

 Date



 John P. Lee
 Chief Cadastral Surveyor for Nebraska