



Heese Rasmussen Land Surveying, LLC
 HC 63 Box 20 O'Neill, Nebraska 68763
 Phone/Fax: (402) 482-5851

This plat was prepared at the request of Mr. Bob Thompson, O'Neill, Nebraska.

FIELD NOTES

- Point # 2 - Found 1" Iron Pipe, as recorded by John I. Steffen, LS #488, dated 01/24/1996.
 - Point # 6 & 7- Found star drill holes, as recorded by Douglas J Stevenson, LS #485, dated 07/14/1993.
 - Point # 8 - Found 1" Iron Pipe.
 - Point # 9 - Found 1/2" Rebar, as recorded by Robert D. Heese, LS #463, dated 04/13/1998.
 - Point # 10 - Found 5/8" Iron Bar, as recorded by John I. Steffen, LS #488, dated 01/24/1996.
 - Point # 11 - Found PK Nail, as recorded by Robert D. Heese, LS # 463, dated 04/13/1998.
 - Point # 12 - Computed point on line between points# 2 and #10 , 69 feet distant from point# 2 .
 - Point # 13 - Computed point on line and at proportionate distance between points #12 and #10.
 - Point # 14 - Set concrete nail on line between points # 2 and #10, 20 feet distant from point #13.
 - Point # 15 - Computed point on line and at proportionate distance between points #8 and #9.
 - Point # 16 - Computed point on line between points #15 and #9, 20 feet distant from point #15.
 - Point # 17 - Computed point on line and at proportionate distance between points #16 and #9.
 - Point # 18 - Computed point on line and at proportionate distance between points #10 and #11.
 - Point # 19 - Computed point on line and at proportionate distance between points #17 and #18.
 - Point # 20 - Computed point on line and at proportionate distance between points #19 and #6.
 - Point # 21 - Computed point on line and at proportionate distance between points #10 and #14.
 - Point # 22 - Set concrete nail on line between points #6 and #14, 10 feet distant from point #6.
 - Point # 23 - Computed point on line between points #20 and #21, 10 feet distant from point #20.
 - Point #24 - Computed point on line between points #23 and #22, 13.5 feet distant from point #23.
 - Point #28 - The northeast corner of Lot 29, Block 21, computed on line and at proportionate distance between points #14 and #21. Unable to monument location. Corner location is located 0.66 feet west of the southeast corner of a building and 0.08 feet north of the south edge of said building. (See Detail).
 - Point # 29 - Set 5/8"X30" Rebar on line and at proportionate distance between points #22 and #24
- Missing point numbers are survey travers points or used for computations.

DESCRIPTION

Lot 29, Fahy's Subdivision of Lots 1, 2, 3, & 4, Block 21, Original Town of O'Neill, Holt County, Nebraska.

SURVEYOR'S CERTIFICATE

I, Robert D. Heese, a registered surveyor of the State of Nebraska, hereby certify that this survey was made by me or under my direct supervision on April 19th, 2002; that all dimensions are in feet and are correct to the best of my knowledge and belief.

Robert D. Heese, Nebraska L.S. #483
 Heese Rasmussen Land Surveying, LLC



| | | | |
|------------|-----------|----------|-----|
| Date | 04/20/02 | Drawn By | SLR |
| Project # | HR544 | | |
| Scale | 1" = 60' | | |
| Field Book | 02 | | |
| File Name | Lot29.dwg | | |
| Revision | | | |
| Revision | | | |
| Sheet | 2 of 2 | | |

Handwritten initials/signature