

Rec'd and filed Nov. 1919
G.L. Blumway Com.
By Robert H. H. H.

4-679

A-2

FIELD NOTES

~~XXXXXX SURVEY XXXX XXXX~~

RETRACEMENT RESURVEY

of the

SUBDIVISION

of

TOWNSHIP 22 NORTH,

RANGE 26 WEST

Of the Sixth Principal Meridian,

In the State of Nebraska

EXECUTED BY

D. A. Nippell and E. T. Best, Jr., U.S. Transitmen,

In the capacity of U. S. Surveyors, under instructions dated June 1st 1915
April 30th, 1915,

issued by N. B. Sweitzer, Asst. Supervisor of Surveys, re
~~XXXXXX United States Surveyors General~~ to govern surveys included in
Group No. 3, which were approved by the Commissioner of the General Land

Office, 1915, pursuant to authority contained in Act
of Congress of March 3, 1909 (35 Stats., 845) amended by joint resolution
of June 25, 1910 (36 Stats., 884).

ReSurvey commenced July 16th, 1915.

ReSurvey completed July 26th, 1915.

Authorized by letters of Commissioner, "E" CLDB 333650 June 17, 1913, and
"E" JSW 327043 June 30, 1913.

6-151

7-25

Retracement Resurvey
 Subdivision of Township 22 North, Range 26 West.

INDEX DIAGRAM.

Township 22 North, Range 26 West.

6	5	4	3	2	1	23	22	15	11	8
7	8	9	10	11	12	22	21	18	14	7
18	17	16	15	14	13	21	20	17	14	10
19	20	21	22	23	24	20	19	16	13	9
30	29	28	27	26	25	19	18	15	12	8
31	32	33	34	35	36	18	17	14	11	7

6-161

6	5	4	3	2	1	7/26-15	7/26-15	7/26-15	7/26-15	7/26-15
7	8	9	10	11	12	7/26-15	7/26-15	7/26-15	7/26-15	7/26-15
18	17	16	15	14	13	7/26-15	7/26-15	7/26-15	7/26-15	7/26-15
19	20	21	22	23	24	7/26-15	7/26-15	7/26-15	7/26-15	7/26-15
30	29	28	27	26	25	7/26-15	7/26-15	7/26-15	7/26-15	7/26-15
31	32	33	34	35	36	7/26-15	7/26-15	7/26-15	7/26-15	7/26-15

Lines along which dates are colored red were surveyed
 by D. A. Nippell, U. S. Transitman.
 Lines along which dates are colored green were surveyed
 by E. T. Best, Jr., U. S. Transitman.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Survey commenced July 16, 1915, and executed with a Keuffel & Esser solar transit No. 20578 and an Ainsworth transit No. 2661 CD, the horizontal limbs of which are provided with two verniers placed opposite each other reading to single minutes of arc, which is also the least count of the latitude and declination arcs of the solar attachment.

These instruments were examined and approved by the Assistant Supervisor of Surveys for District No. 3 at Neligh, Nebraska, and, prior to the commencement of this work, all adjustments of the transits were tested and existing errors corrected. The tapes were compared at frequent intervals with a standard furnished by the Commissioner of the General Land Office.

All lines, when necessary, were double back and fore sight transit lines, run as rhumb lines on the ground by correcting the tangent with offsets as indicated in the table for the latitude of this township, thus giving all lines their true bearings and distances. As search revealed evidence of the original subdivision survey, all such corners found were restored in their original positions and the lost corners were located by proportional measurement, based upon the original plat and field notes, which determined their true courses and distances. This gives each section its proper measurements without carrying any accumulative excess or deficiency into any portion of the township, which would accrue if the regular method of subdivision were followed.

In writing the field notes, I commence at the southwest corner of section 36 and run the lines northward and eastward, in sequence, as did the original deputy. Temporary lines and preliminary calculations have been omitted for purposes of brevity of clarification; and the actual courses and distances recorded as the true azimuths and measurements of this survey. This simplifies the records, obviates all confusion for the land owner who is the one primarily concerned and fulfills the mandates of the courts, which prescribe the following of the actual footsteps of the original surveyor.

Upon initiating this survey, to establish a meridian to determine my courses, I turn a line from the exteriors and later check my courses with the following observation on Polaris at eastern elongation:
Lat. (approx.) = 41° 54' N. Long. (approx.) = 100° 18' W.

Observation taken on line bet. secs. 2 and 3, T. 22 N., R. 26 W., July 22, 1915. D. A. Nippell, observer.

Mark, about 20 chains northward on knoll. Atmosphere, clear; no haze, no wind.

Watch, 90th meridian time; checked with W.U. Telegraph time and found to be 30^s fast.

Angle, star to mark	Watch time
Direct 2° 01' .0 left of star	12 ^m 14 ^m 30 ^s a.m.
Reverse 2 01 0	12 17 00
Direct 2 01 0	12 20 00
Reverse 2 01 0	12 22 00
Mean angle and time 2° 01' .0	12 ^m 18 ^m 23 ^s a.m.
Watch correction	- 0 0 30
Longitude correction	- 0 41 12
L.m.t. observation July 22	11 ^m 36 ^m 41 ^s a.m.
Azimuth of Polaris at observation	N. 1° 32' .6 E.
Mean angle, star to mark	2° 01' .0
Azimuth of Polaris	1 32 6
Bearing of observation line	N. 0° 28' .4 W.

As my course is supposed to be N. 0° 28' W. and the observation shows a difference of but 0'.4, I assume that my courses are satisfactorily established.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

I commence the retracement resurvey of the subdivision of T. 22 N., R. 26 W. at the reestablished cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., prev. described, using a line turned from the exteriors. At the SE. cor. of this Tp., lat. $41^{\circ}50'$ N., long. $100^{\circ}16'$ W., the mean magnetic bearing of my meridian is $12^{\circ}15'$ W.; hence, the mean magnetic declination is $12^{\circ}15'$ east. Resurvey commenced July 16, 1915.

From the reestablished cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., prev. described, N. $0^{\circ}12'$ E., bet. secs. 35 and 36.

Over high broken hills.
39.95 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 36 on E., and S 35 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 35 and 36.

79.91 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 25, 26, 35 and 36, and mark on top of brass cap, R 26 W S 25 in NE., S 36 in SE., S 35 in SW., and T 22 N S 26 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor. Land, high broken hills. Soil, sandy; 4th rate. No timber.

From this sec. cor., S. $89^{\circ}47'$ E., bet. secs. 25 and 36.

Over high broken hills.
39.72 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 25 1/4 on N., and S 36 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 25 and 36.

79.45 Intersect the reestablished cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., prev. described. Land, high broken hills. Soil, sandy; 4th rate. No timber.

From the cor. of secs. 25, 26, 35 and 36, prev. described,

North, bet. secs. 25 and 26.

Over high broken hills.
39.95 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 25 on E., and S 26 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 25 and 26.

79.91 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 23, 24,

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

25 and 26, and mark on top of brass cap,
R 26 W S 24 in NE.,
S 25 in SE.,
S 26 in SW., and
T 22 N S 23 in NW., quadrant of cap; dig pits, 20
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°42' E., bet. secs. 24 and 25.
Over high broken hills.
40.00 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 24 1/4 on N., and
S 25 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 24 and 25.
80.00 Intersect the reestablished cor. of secs. 19, 24, 25 and
30, on the E. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 23, 24, 25 and 26, prev.
described,
N. 0°7' E., bet. secs. 23 and 24.
Over high broken hills.
39.95 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 24 on E., and
S 23 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 23 and 24.
79.91 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 13, 14,
23 and 24, and mark on top of brass cap,
R 26 W S 13 in NE.,
S 24 in SE.,
S 23 in SW., and
T 22 N S 14 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°36' E., bet. secs. 13 and 24.
Over high broken hills.
40.19 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 13 1/4 on N., and
S 24 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 13 and 24.
80.38 Intersect the reestablished cor. of secs. 13, 18, 19 and
24, on the E. bdy. of the Tp., prev. described.
Land, high broken hills.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 13, 14, 23 and 24, prev.
described,
North, bet. secs. 13 and 14.
Over high broken hills.
39.95 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 13 on E., and
S 14 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 13 and 14.
79.91 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 11, 12,
13 and 14, and mark on top of brass cap,
R 26 W S 12 in NE.,
S 13 in SE.,
S 14 in SW., and
T 22 N S 11 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°36' E., bet. secs. 12 and 13.
Over high broken hills.
40.26 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 12 1/4 on N., and
S 13 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 12 and 13.
80.52 Intersect the restored cor. of secs. 7, 12, 13 and 18, on
the E. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 11, 12, 13 and 14, prev.
described,
North, bet. secs. 11 and 12.
Over high broken hills.
39.95 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 12 on E., and
S 11 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 11 and 12.
79.91 Intersect the original cor. of secs. 1, 2, 11 and 12; no
evidence above ground; remove sod and find outlines of
original pits, 24x24 ins., in each sec., 8 1/2 lks.
dist. from intersection of lines connecting same. At
this point, I set an iron post, 3 ft. long, 2 ins. dia.,
two feet in the ground in cement base, 8x8x6 ins., for
the restored cor. of secs. 1, 2, 11 and 12, and mark
on top of brass cap,
R 26 W S 1 in NE.,
S 12 in SE.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains. S 11 in SW., and
T 22 N S 2 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°33' E., bet. secs. 1 and 12.
Over high broken hills.

- 3.45 Enter rolling valley.
- 40.16 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 1 1/4 on N., and
S 12 on S., half of cap; dig pits, 20x20x15 ins.,
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 1 and 12.
- 78.10 Right bank of Middle Loup River, which is a stream of clear
water, 3 ft. deep; course SE.
- 80.33 Intersect the point for the cor. of secs. 1, 6, 7 and 12,
on the E. bdy. of the Tp., prev. described, which is
N. 11' W. 88 lks. from the C. to this sec. cor.
Land, high broken hills and rolling valley.
Soil, sandy; 3rd and 4th rate.
No timber.

From the cor. of secs. 1, 2, 11 and 12, prev.
described,
N. 0°11' W., bet. secs. 1 and 2.
Over high broken hills.

- 4.00 Enter rolling valley.
- 13.40 Right bank of Middle Loup River, a stream of clear water,
3 ft. deep; course East.
- 17.20 Left bank of Middle Loup River, thence over rolling valley.
- 26.50 Wagon road bet. Theford and Halsey, Nebr., bears NW. and SE.
- 27.80 Center of C.B. & C.R.R. track, bears NW. and SE.
- 30.00 Leave valley; thence over high broken hills.
- 39.68 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 1 on E., and
S 2 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 1 and 2.
- 79.35 Intersect the restored cor. of secs. 1, 2, 35 and 36, on
the N. bdy. of the Tp., prev. described.
Land, high broken hills and rolling valley.
Soil, sandy; 3rd and 4th rate.
No timber.

From the reestablished cor. of secs. 2, 3, 34 and
35, on the S. bdy. of the Tp., prev. described,
N. 0°10' E., bet. secs. 34 and 35.
Over high broken hills.

- 39.89 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 35 on E., and
S 34 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 34 and 35.
- 79.79 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains. 8x8x6 ins., for the reestablished cor. of secs. 26, 27,
34 and 35, and mark on top of brass cap,
R 26 W S 26 in NE.,
S 35 in SE.,
S 34 in SW., and
T 22 N S 27 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°58' E., bet. secs. 26 and 35.
Over high broken hills.

- 39.59 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 26 1/4 on N., and
S 35 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 26 and 35.
- 79.19 Intersect the reestablished cor. of secs. 25, 26, 35 and
36, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 26, 27, 34 and 35, prev.
described,
N. 0°10' W., bet. secs. 26 and 27.
Over high broken hills.

- 39.89 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 26 on E., and
S 27 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 26 and 27.
- 79.79 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 22, 23,
26 and 27, and mark on top of brass cap,
R 26 W S 23 in NE.,
S 26 in SE.,
S 27 in SW., and
T 22 N S 22 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
N. 89°57' E., bet. secs. 25 and 26.
Over high broken hills.

- 39.69 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 23 1/4 on N., and
S 26 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 23 and 26.
- 79.39 Intersect the reestablished cor. of secs. 23, 24, 25 and
26, prev. described.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 22, 23, 26 and 27, prev. described,
North, bet. secs. 22 and 23.

39.89 Over high broken hills.
The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 23 on E., and
S 22 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.

79.79 Thence I continue bet. secs. 22 and 23.
The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 14, 15, 22 and 23, and mark on top of brass cap,
R 26 W S 14 in NE.,
S 23 in SE.,
S 22 in SW., and
T 22 N S 15 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
N. 89°51' E., bet. secs. 14 and 23.

39.76 Over high broken hills.
The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 14 1/4 on N., and
S 23 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.

79.53 Thence I continue bet. secs. 14 and 23.
Intersect the reestablished cor. of secs. 13, 14, 23 and 24, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 14, 15, 22 and 23, prev. described,

N. 0°18' W., bet. secs. 14 and 15.
39.89 Over high broken hills.
The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 14 on E., and
S 15 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.

79.79 Thence I continue bet. secs. 14 and 15.
The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 10, 11, 14 and 15, and mark on top of brass cap,
R 26 W S 11 in NE.,
S 14 in SE.,
S 15 in SW., and
T 22 N S 10 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
N. 89°46' E., bet. secs. 11 and 14.

39.97 Over high broken hills.
The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 11 1/4 on N., and
S 14 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.

79.94 Thence I continue bet. secs. 11 and 14.
Intersect the reestablished cor. of secs. 11, 12, 13 and 14, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 10, 11, 14 and 15, prev. described,

N. 0°6' W., bet. secs. 10 and 11.
39.89 Over high broken hills.
The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 11 on E., and
S 10 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.

79.79 Thence I continue bet. secs. 10 and 11.
The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 2, 3, 10 and 11, and mark on top of brass cap,
R 26 W S 2 in NE.,
S 11 in SE.,
S 10 in SW., and
T 22 N S 3 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
N. 89°41' E., bet. secs. 2 and 11.

40.03 Over high broken hills.
The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 2 1/4 on N., and
S 11 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.

80.06 Thence I continue bet. secs. 2 and 11.
Intersect the restored cor. of secs. 1, 2, 11 and 12, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 2, 3, 10 and 11, prev. described,

N. 0°28' W., bet. secs. 2 and 3.
Over high broken hills.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains.
13.00 Enter rolling valley of Middle Loup River.
Supervisor's Headquarters, Bessey Nurseries, Nebraska.
National Forest, cement 2-story building, 30x30 ft.,
bears West 0.85 chs.
14.00 SE. corner of Bessey Nurseries.
19.00 NE. corner of Bessey Nurseries.
21.00 Right bank of Middle Loup River, which is a stream of clear
water, 3 ft. deep; course East.
23.15 Left bank of Middle Loup River; thence over rolling valley.
39.90 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 2 on E., and
S 3 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 2 and 3.
40.20 Wagon road bet. Theford and Halsey, Nebr., bears NW. & SE.
41.50 Center of C.B. & Q.R.R. track, bears NW. and SE.
44.00 Leave valley; thence over rolling hills.
80.17 Intersect the reestablished cor. of secs. 2, 3, 34 and 35,
on the N. bdy. of the Tp., prev. described.
Land, rolling valley, rolling and high broken hills.
Soil, sandy; 3rd and 4th rate.
No timber.

- From the reestablished cor. of secs. 3, 4, 33 and
34, on the S. bdy. of the Tp., prev. described,
N. 0°4' W., bet. secs. 33 and 34.
Over high broken hills.
39.85 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 34 on E., and
S 33 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 33 and 34.
79.71 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 27, 28,
33 and 34, and mark on top of brass cap,
R 26 W S 27 in NE.,
S 34 in SE.,
S 33 in SW., and
T 22 N S 28 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

- From this sec. cor.,
S. 89°57' E., bet. secs. 27 and 34.
Over high broken hills.
39.75 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 27 1/4 on N., and
S 34 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 27 and 34.
79.50 Intersect the reestablished cor. of secs. 26, 27, 34 and
35, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 27, 28, 33 and 34, prov.
described.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains.
N. 0°35' W., bet. secs. 27 and 28.
Over high broken hills.
39.85 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 27 on E., and
S 28 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 27 and 28.
79.71 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 21, 22,
27 and 28, and mark on top of brass cap,
R 26 W S 22 in NE.,
S 27 in SE.,
S 28 in SW., and
T 22 N S 21 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

- From this sec. cor.,
East, bet. secs. 22 and 27.
Over high broken hills.
40.03 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 22 1/4 on N., and
S 27 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 22 and 27.
80.06 Intersect the reestablished cor. of secs. 22, 23, 26 and
27, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

- From the cor. of secs. 21, 22, 27 and 28, prev.
described,
N. 0°16' W., bet. secs. 21 and 22.
Over high broken hills.
39.85 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 22 on E., and
S 21 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 21 and 22.
79.71 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 15, 16,
21 and 22, and mark on top of brass cap,
R 26 W S 15 in NE.,
S 22 in SE.,
S 21 in SW., and
T 22 N S 16 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains. N. 89°57' E., bet. secs. 15 and 22.
Over high broken hills.
- 40.21 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 15 1/4 on N., and S 22 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 15 and 22.
- 80.42 Intersect the reestablished cor. of secs. 14, 15, 22 and 23, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 15, 16, 21 and 22, prev. described,

- N. 0°32' W., bet. secs. 15 and 16.
Over high broken hills.
- 39.85 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 15 on E., and S 16 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 15 and 16.
- 79.71 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 9, 10, 15 and 16, and mark on top of brass cap, R 26 W S 10 in NE., S 15 in SE., S 16 in SW., and T 22 N S 9 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
N. 89°53' E., bet. secs. 10 and 15.
Over high broken hills.

- 40.35 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 10 1/4 on N., and S 15 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 10 and 15.
- 80.71 Intersect the reestablished cor. of secs. 10, 11, 14 and 15, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 9, 10, 15 and 16, prev. described,

- N. 0°25' W., bet. secs. 9 and 10.
Over high broken hills.
- 39.85 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 10 on E., and S 9 1/4 on W., half of cap; dig pits, 20x20x15

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains. ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 9 and 10.
- 79.71 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 3, 4, 9 and 10, and mark on top of brass cap, R 26 W S 3 in NE., S 10 in SE., S 9 in SW., and T 22 N S 4 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,

- N. 89°50' E., bet. secs. 3 and 10.
Over high broken hills.
- 40.56 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 3 1/4 on N., and S 10 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 3 and 10.
- 81.12 Intersect the reestablished cor. of secs. 2, 3, 10 and 11, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 3, 4, 9 and 10, prev. described,

- N. 0°13' E., bet. secs. 3 and 4.
Over high broken hills.
- 39.85 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 3 on E., and S 4 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 3 and 4.
- 42.75 Enter rolling valley of Middle Loup River.
- 80.40 Intersect the reestablished cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., prev. described.
Land, high broken hills and rolling valley.
Soil, sandy; 4th rate.
No timber.

From the reestablished cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., prev. described,
N. 0°28' W., bet. secs. 32 and 33.
Over high broken hills.

- 39.84 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap, S 33 on E., and S 32 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor. Thence I continue bet. secs. 32 and 33.
- 79.69 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 28, 29,

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

32 and 33, and mark on top of brass cap,
R 26 W S 28 in NE.,
S 33 in SE.,
S 32 in SW., and
T 22 N S 29 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°54' E., bet. secs. 28 and 33.
Over high broken hills.

39.86 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 28 1/4 on N., and
S 33 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

79.72 Thence I continue bet. secs. 28 and 33.
Intersect the reestablished cor. of secs. 27, 28, 33 and
34, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 28, 29, 32 and 33, prev.
described,
N. 0°47' W., bet. secs. 28 and 29.
Over high broken hills.

39.84 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 28 on E., and
S 29 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.

79.69 Thence I continue bet. secs. 28 and 29.
The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 20, 21,
28 and 29, and mark on top of brass cap,
R 26 W S 21 in NE.,
S 28 in SE.,
S 29 in SW., and
T 22 N S 20 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°55' E., bet. secs. 21 and 28.
Over high broken hills.

39.98 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 21 1/4 on N., and
S 28 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

79.97 Thence I continue bet. secs. 21 and 28.
Intersect the reestablished cor. of secs. 21, 22, 27 and
28, prev. described.
Land, high broken hills.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 20, 21, 28 and 29, prev.
described,

N. 0°19' W., bet. secs. 20 and 21.
Over high broken hills.

39.84 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 21 on E., and
S 20 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.

79.69 Thence I continue bet. secs. 20 and 21.
The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 16, 17,
20 and 21, and mark on top of brass cap,
R 26 W S 16 in NE.,
S 21 in SE.,
S 20 in SW., and
T 22 N S 17 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°56' E., bet. secs. 16 and 21.
Over high broken hills.

40.01 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 16 1/4 on N., and
S 21 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

80.02 Thence I continue bet. secs. 16 and 21.
Intersect the reestablished cor. of secs. 15, 16, 21 and
22, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 16, 17, 20 and 21, prev.
described,

N. 0°37' W., bet. secs. 16 and 17.
Over high broken hills.

39.84 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 16 on E., and
S 17 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.

79.69 Thence I continue bet. secs. 16 and 17.
The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 8, 9,
16 and 17, and mark on top of brass cap,
R 26 W S 9 in NE.,
S 16 in SE.,
S 17 in SW., and
T 22 N S 8 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°57' E., bet. secs. 9 and 16.

Over high broken hills.
40.05 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 9 1/4 on N., and
S 16 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

Thence I continue bet. secs. 9 and 16.
80.11 Intersect the reestablished cor. of secs. 9, 10, 15 and 16,
prev. described.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 8, 9, 16 and 17, prev.
described,

N. 0°22' W., bet. secs. 8 and 9.

Over high broken hills.
39.84 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 9 on E., and
S 8 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.

Thence I continue bet. secs. 8 and 9.
79.69 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 4, 5,
8 and 9, and mark on top of brass cap,
R 26 W S 4 in NE.,
S 9 in SE.,
S 8 in SW., and
T 22 N S 5 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°58' E., bet. secs. 4 and 9.

Over high broken hills.
40.01 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 4 1/4 on N., and
S 9 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

Thence I continue bet. secs. 4 and 9.
80.03 Intersect the reestablished cor. of secs. 3, 4, 9 and 10,
prev. described.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 4, 5, 8 and 9, prev.
described,

N. 0°17' E., bet. secs. 4 and 5.

Over high broken hills.
39.85 The proportionate distance, I set an iron post, 3 ft. long,

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 4 on E., and
S 5 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.

Thence I continue bet. secs. 4 and 5.
80.51 Intersect the reestablished cor. of secs. 4, 5, 32 and 33,
on the N. bdy. of the Tp., prev. described.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the reestablished cor. of secs. 5, 6, 31 and
32, on the S. bdy. of the Tp., prpv. described,
N. 0°31' W., bet. secs. 31 and 32.

Over high broken hills.
39.89 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 32 on E., and
S 31 1/4 on W., half of cap; dig pits, 20x20x15
ins., N. & S. of post, 7 ft. dist.; and raise a mound
of earth, 4 ft. base, 2 ft. high, around cor.

Thence I continue bet. secs. 31 and 32.
79.79 The proportionate distance, I set an iron post, 3 ft. long,
2 ins. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished cor. of secs. 29, 30,
31 and 32, and mark on top of brass cap,
R 26 W S 29 in NE.,
S 32 in SE.,
S 31 in SW., and
T 22 N S 30 in NW., quadrant of cap; dig pits,
20x20x15 ins., in each sec., 7 ft. dist.; and raise a
mound of earth, 6 ft. base, 2 ft. high, around cor.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°49' E., bet. secs. 29 and 32.

Over high broken hills.
39.60 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 29 1/4 on N., and
S 32 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

Thence I continue bet. secs. 29 and 32.
79.21 Intersect the reestablished cor. of secs. 28, 29, 32 and
33, prev. described.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 29, 30, 31 and 32, prev.
described,
N. 89°55' W., bet. secs. 30 and 31.

Over high broken hills.
39.66 The proportionate distance, I set an iron post, 3 ft. long,
1 in. dia., two feet in the ground in cement base,
8x8x6 ins., for the reestablished 1/4 sec. cor., and
mark on top of brass cap,
S 30 1/4 on N., and
S 31 on S., half of cap; dig pits, 20x20x15 ins.,
E. & W. of post, 7 ft. dist.; and raise a mound of
earth, 4 ft. base, 2 ft. high, around cor.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

Thence I continue bet. secs. 30 and 31.
80.46 Intersect the reestablished cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 29, 30, 31 and 32, prev. described.

N. $0^{\circ}46'$ W., bet. secs. 29 and 30.
Over high broken hills.
59.89 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 29 on E., and
S 30 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
79.79 Thence I continue bet. secs. 29 and 30.
Intersect the original cor. of secs. 19, 20, 29 and 30; no evidence above ground; remove sod and find outlines of original pits, 24x24 ins., in each sec., 8 1/2 lks. dist. from intersection of lines connecting same. At this point, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the restored cor. of secs. 19, 20, 29 and 30, and mark on top of brass cap,
R 26 W S 20 in NE.,
S 29 in SE.,
S 30 in SW., and
T 22 N S 19 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. $89^{\circ}44'$ E., bet. secs. 20 and 29.
Over high broken hills.

39.59 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 20 1/4 on N., and
S 29 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 20 and 29.
79.18 Intersect the reestablished cor. of secs. 20, 21, 28 and 29, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 19, 20, 29 and 30, prev. described.

N. $89^{\circ}56'$ W., bet. secs. 19 and 30.
Over high broken hills.
39.83 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 19 1/4 on N., and
S 30 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 19 and 30.
80.45 Intersect the reestablished cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., prev. described.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

Chains.

Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 19, 20, 29 and 30, prev. described.

N. $0^{\circ}55'$ W., bet. secs. 19 and 20.
Over high broken hills.
59.86 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 20 on E., and
S 19 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 19 and 20.
79.73 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 17, 18, 19 and 20, and mark on top of brass cap,
R 26 W S 17 in NE.,
S 20 in SE.,
S 19 in SW., and
T 22 N S 18 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. $89^{\circ}43'$ E., bet. secs. 17 and 20.
Over high broken hills.

39.76 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 17 1/4 on N., and
S 20 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 17 and 20.
79.53 Intersect the reestablished cor. of secs. 16, 17, 20 and 21, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 17, 18, 19 and 20, prev. described.

N. $89^{\circ}55'$ W., bet. secs. 18 and 19.
Over high broken hills.
39.96 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 18 1/4 on N., and
S 19 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 18 and 19.
80.68 Intersect the reestablished cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 17, 18, 19 and 20, prev. described.

N. $0^{\circ}41'$ W., bet. secs. 17 and 18.
Over high broken hills.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains.
- 39.86 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 17 on E., and
S 18 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 17 and 18.
- 79.73 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 7, 8, 17 and 18, and mark on top of brass cap,
R 26 W S 8 in NE.,
S 17 in SE.,
S 18 in SW., and
T 22 N S 7 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°41' E., bet. secs. 8 and 17.
Over high broken hills.

- 39.80 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 8 1/4 on N., and
S 17 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 8 and 17.
- 79.61 Intersect the reestablished cor. of secs. 8, 9, 16 and 17, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 7, 8, 17 and 18, prev. described,
N. 89°54' W., bet. secs. 7 and 18.
Over high broken hills.

- 40.06 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 7 1/4 on N., and
S 18 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 7 and 18.
- 80.80 Intersect the reestablished cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

- From the cor. of secs. 7, 8, 17 and 18, prev. described,
N. 0°44' W., bet. secs. 7 and 8.
Over high broken hills.
- 39.86 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 8 on E., and
S 7 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains.
- of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 7 and 8.
- 79.73 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 5, 6, 7 and 8, and mark on top of brass cap,
R 26 W S 5 in NE.,
S 8 in SE.,
S 7 in SW., and
T 22 N S 6 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From this sec. cor.,
S. 89°40' E., bet. secs. 5 and 8.
Over high broken hills.

- 40.05 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 5 1/4 on N., and
S 8 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 5 and 8.
- 80.10 Intersect the reestablished cor. of secs. 4, 5, 8 and 9, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 5, 6, 7 and 8, prev. described,

- N. 89°53' W., bet. secs. 6 and 7.
Over high broken hills.
- 40.17 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 6 1/4 on N., and
S 7 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 6 and 7.
- 80.82 Intersect the reestablished cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

From the cor. of secs. 5, 6, 7 and 8, prev. described,

- N. 0°24' E., bet. secs. 5 and 6.
Over high broken hills.
- 39.87 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 5 on E., and
S 6 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 5 and 6.
- 80.21 Intersect the restored cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains.
- 39.86 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 17 on E., and
S 18 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 17 and 18.
- 79.73 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 7, 8, 17 and 18, and mark on top of brass cap,
R 26 W S 8 in NE.,
S 17 in SE.,
S 18 in SW., and
T 22 N S 7 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.
-
- From this sec. cor.,
S. 89°41' E., bet. secs. 8 and 17.
Over high broken hills.
- 39.80 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 8 1/4 on N., and
S 17 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 8 and 17.
- 79.61 Intersect the reestablished cor. of secs. 8, 9, 16 and 17, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.
-
- From the cor. of secs. 7, 8, 17 and 18, prev. described,
N. 89°54' W., bet. secs. 7 and 18.
Over high broken hills.
- 40.06 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 7 1/4 on N., and
S 18 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 7 and 18.
- 80.80 Intersect the reestablished cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.
-
- From the cor. of secs. 7, 8, 17 and 18, prev. described,
N. 0°44' W., bet. secs. 7 and 8.
Over high broken hills.
- 39.86 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 8 on E., and
S 7 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

- Chains.
- of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 7 and 8.
- 79.73 The proportionate distance, I set an iron post, 3 ft. long, 2 ins. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished cor. of secs. 5, 6, 7 and 8, and mark on top of brass cap,
R 26 W S 5 in NE.,
S 8 in SE.,
S 7 in SW., and
T 22 N S 6 in NW., quadrant of cap; dig pits, 20x20x15 ins., in each sec., 7 ft. dist.; and raise a mound of earth, 6 ft. base, 2 ft. high, around cor.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.
-
- From this sec. cor.,
S. 89°40' E., bet. secs. 5 and 8.
Over high broken hills.
- 40.05 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 5 1/4 on N., and
S 8 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 5 and 8.
- 80.10 Intersect the reestablished cor. of secs. 4, 5, 8 and 9, prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.
-
- From the cor. of secs. 5, 6, 7 and 8, prev. described,
N. 89°53' W., bet. secs. 6 and 7.
Over high broken hills.
- 40.17 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 6 1/4 on N., and
S 7 on S., half of cap; dig pits, 20x20x15 ins., E. & W. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 6 and 7.
- 80.82 Intersect the reestablished cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.
-
- From the cor. of secs. 5, 6, 7 and 8, prev. described,
N. 0°24' E., bet. secs. 5 and 6.
Over high broken hills.
- 39.87 The proportionate distance, I set an iron post, 3 ft. long, 1 in. dia., two feet in the ground in cement base, 8x8x6 ins., for the reestablished 1/4 sec. cor., and mark on top of brass cap,
S 5 on E., and
S 6 1/4 on W., half of cap; dig pits, 20x20x15 ins., N. & S. of post, 7 ft. dist.; and raise a mound of earth, 4 ft. base, 2 ft. high, around cor.
Thence I continue bet. secs. 5 and 6.
- 80.21 Intersect the restored cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., prev. described.
Land, high broken hills.
Soil, sandy; 4th rate.
No timber.

Retracement resurvey,
Subdivision of Township 22 North, Range 26 West.

GENERAL DESCRIPTION.

Except for a few small rolling valleys along the boundaries of this township, the only valley land is that along the Middle Loup River. The remainder consists entirely of high broken hills. The soil in the hills is a fourth rate sand; that in the valleys is a third rate sand. The hills are sparsely covered with wild grasses and are suitable for grazing only. The valleys are, in their natural state, covered with such wild grasses as bunch and blue stem and are good hay lands; with proper care and cultivation, good crops of corn and small grain can also be raised on them. The valley of the Middle Loup River is situated in the northeastern part of this township and is of a rolling character. It varies in width from one-half a mile to a mile.

The only natural body of water in this township is the Middle Loup River. This stream of clear water is about three feet deep and from two to three chains wide. It enters this area in section 3 and leaves it at the corner of secs. 1 and 12 on the east boundary. It flows in a south-east direction to a point a little south of the center of section 3 where it turns and flows a little south of east until it leaves this township. The settlers obtain water for domestic purposes from wells driven to a moderate depth.

The Bessey Nursery, which is maintained by the Government to raise trees for the Nebraska National Forest in Thomas and Blaine Counties is situated on the south bank of the Middle Loup River in Section 3.

The hamlet of Halsey, with a population of about thirty people, is situated on the east boundary of this township in section 1. Part of it lies in Blaine and part in Thomas County.

The Chicago, Burlington & Quincy Railroad runs up the north side of the Middle Loup River, passing along the southern outskirts of Halsey and running in a northwest and southeast direction.

Resurvey completed July 26, 1915.

CERTIFICATE OF ASSISTANTS.

We, the undersigned, hereby certify upon honor that we assisted, to the best of our skill and ability, D. A. Nippell, U. S. Surveyor, during the periods and in the capacities stated opposite our several signatures, in surveying all those parts or portions of

Subdivisional lines of Township 22 North, Range 26 West

of the Sixth Principal Meridian, in the State of Nebraska which are represented in the foregoing field notes as having been executed by him, and under his direction; and that said survey has been, in all respects, to the best of our knowledge and belief, well and faithfully executed.

Table with columns: NAME, PERIOD OF SERVICE (BEGUN, ENDED), CAPACITY. Includes names like A. M. Sellery, T. A. Stuckey, F. C. Reavis, Geo. E. Kline, Earl Ketcham, Kirk Tessier, J. J. McPhaul, C. C. Golden, E. T. Best, Jr.

Subscribed and certified to before me on the dates of the final service as shown above.

D. A. Nippell, U. S. Surveyor.

FINAL OATH OF UNITED STATES SURVEYOR.

I, ^{Transitman} D. A. Nippell, U. S. Surveyor, do solemnly swear that, in pursuance of assignment received from ~~U. S. Surveyor~~ N. B. Sweitzer, Asst. Supervisor of Surveys, of special instructions received from ~~U. S. Surveyor~~ ^{re} bearing date of the 30th day of June, 1915, I have well, faithfully, and truly, in my own proper person, and in strict conformity with said instructions, the Manual of Surveying Instructions, and the laws of the United States, surveyed all those parts or portions of

Subdivisional lines of Township 22 North, Range 26 West

of the Sixth

Principal Meridian, in the State of Nebraska, which are represented in and index diagram on page 1 of same and on the dates shown on said the foregoing field notes, as having been executed by me, and under my direction; and I do further diagram ^{re} solemnly swear that all the corners of said survey have been established and perpetuated in strict accordance with the Manual of Surveying Instructions, and the special written instructions of the ~~U. S. Surveyor~~ ^{re} Asst. Supervisor and in the specific manner described in the field notes, and that the foregoing are the original field notes of such survey.

D. A. Nippell

U. S. ~~Surveyor~~ Transitman

Subscribed by said D. A. Nippell, and sworn to before me } this 8th day of January, 1917



J. H. Recroft

Clerk Dist. Court

APPROVAL.

Department of the Interior
Office of the United States Surveyor General,
General Land Office, Washington, D.C. June 27, 1917

The foregoing field notes of the survey of ^{re} the subdivision lines of Township 22 N., Range 26 W. 6th P. M., Nebraska.

executed by ^{assignment} D. A. Nippell and E. F. Best, Transitmen, under his special instructions dated April 30, 1915, having been critically examined, and the necessary corrections and explanations made, the said field notes, and the surveys they describe, are hereby approved.

Chas. Gallman
Commissioner Ex officio U. S. Surveyor General for Nebraska

I certify that the foregoing transcript of the field notes of the above-described surveys in Nebraska has been correctly copied from the original notes on file in this office.

Commissioner U. S. Surveyor General