Dependent Resurvey, Portion of the Subdivisional Lines,
T. 26 N., R. 9 E., Sixth Principal Meridian, Nebraska

CHAINS	
29.70	Point for the N-S 1/64 sec. cor. of secs. 5 and 6. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd. T26N R9E N-S 1/64 S 6|S 5 1997 Cor. is located at cor. of fences extending N. and W.
39.60	The 1/4 sec. cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., as described in the 1995 field notes of the dependent resurvey, T. 26 N., R. 9 E.

Dependent Resurvey, Portion of the Subdivision of Section 6,
T. 26 N., R. 9 E., Sixth Principal Meridian, Nebraska

(Restoring the Three Mile Method of survey executed by
John W. Beaman in 1875)

	From the S. 1/16 sec. cor. of secs. 5 and 6. N. 89° 29′ W., on the E. and W. center line of the S½ of sec. 6. Over rolling terrain, across alfalfa field.
2.40	Leave alfalfa field.
4.40	Creek, drains NNW.
19.98	Point for the SE. 1/16 sec. cor. of sec. 6, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd. T26N R9E SE 1/16 S 6 1997